



JXT SERIES

CASE IH
AGRICULTURE

	JX55T	JX75T
ENGINE	IVECO Series 8000	IVECO Series 8000
No. of cylinders / Aspiration	3 CYL NA	4 CYL NA
Displacement (Capacity cm³)	2931	3908
Power (kW / hp) @ 2500 rpm	40 / 55	55 / 75
Max. torque (Nm @ rpm)	184 Nm @ 1500 rpm	242 Nm @ 1500 rpm
Emission Level	Tier 1 (Tier 2 optional)	Tier 1 (Tier 2 optional)
Fuel Tank Capacity	62	62
TRANSMISSION		
Transmission clutch	Mechanical	Mechanical
Total number of speeds	8 forward, 2 reverse	8 forward, 2 reverse
Gearbox features	Constant mesh (optional partial synchromesh)	Constant mesh (optional partial synchromesh)
Optional Speeds (with creeper)	12 forward, 3 reverse	12 forward, 3 reverse
POWER TAKE OFF		
PTO features	Fully independent	Fully independent
PTO speeds (rpm)	540	540
Optional PTO	Group speed	Group speed
HYDRAULICS		
Centre system (close/open)	Open	Open
Max. flow output (l/min) / Max pressure (BAR)	34.0 / 190	34.0 / 190
HYD. POWER LIFT & 3 POINT LINKAGE		
Control system	Mechanical	Mechanical
Control features (Position, Draft etc)	Position / Draft / Mix / Lift O Matic	Position / Draft / Mix / Lift O Matic
Draft Control	Top link	Top link
Max. lift capacity at ball end W/horizon. links (kgs)	Std. 1920	Std. 1920 / opt. 2620
2WD FRONT AXLE		
Axle Type	Inverted U section	Inverted U section
Adjustable tread dimension (mm)	From 1400 to 1810	From 1410 to 1910
Minimum turning radius without braking (m)	3.5	3.6
4WD FRONT AXLE		
Position axle pivoting point	Coaxial	Coaxial
Adjustable tread dimension (mm)	From 1445 to 1875	From 1545 to 1875
Minimum turning radius W/O braking & W/4WD disengaged (m)	5.1	5.2
REAR AXLE		
Axle description	Outboard reduction with wet brakes	Outboard reduction with wet brakes
Adjustable tread dimension (mm)	From 1480 to 2039	From 1520 to 2033
DIMENSIONS & WEIGHT		
Wheel base 2WD / 4WD (mm)	2050 / 2010	2200 / 2160
Shipping weight 2WD rops / 4WD rops (kg)	2230 / 2355	2450 / 2575
Ground clearance under front axle 2WD / 4WD (mm)	500 / 380	500 / 410
Ground clearance under rear axle (mm)	530	555
Height to the top of exhaust 2WD / 4WD	2200 / 2210	2375 / 2385
Type Size 2WD Front/Back	7.5 - 16 / 16.9 - 28	7.50 - 16 / 16.9 - 30
Type Size 4WD Front/Back	9.5 - 24 / 16.9 - 28	11.2 - 24 / 16.9 - 30
OTHER OPTIONAL ITEMS		
Rops, Canopy , Front & Rear Weights	○	○

○ Optional



INTERNATIONAL

SAFETY NEVER HURTS!™ Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided.

This literature has been published for worldwide circulation. The standard and optional equipment and the availability of individual models may vary from one country to the next. Case IH reserves the right to undertake modifications without prior notice to the design and technical equipment at all times without this resulting in any obligation whatsoever to make such modifications to units already sold. Whilst every effort is made to ensure that the specifications, descriptions and illustrations in this brochure are correct at the time of going to press, these are also subject to change without prior notice. Illustrations may show optional equipment or may not show all standard equipment.

CNH International S.A. - Network Development & Advertising - Riva Paradiso, 14 - 6902 Paradiso-Lugano Switzerland
 © 2011 CASE IH - Visit our website: www.caseih.com - Send us an e-mail: International@cnh.com

Published by CNH INTERNATIONAL SA. Communications & Advertising - Printed in Italy - 06/11 - Cod. N. IR8105C/INB

Your Case IH Dealer