

TRUE-TANDEM™ 345 SEED BED DISK HARROW SPECIFICATIONS

CASE IH
AGRICULTURE



TRUE-TANDEM™ 345 SEED BED DISK HARROW SPECIFICATIONS

- The latest generation in disk harrows from Case IH - the industry leader for many years.
- A true seedbed disk for spring or fall
- True-tandem design pulls evenly as opposed to a double-offset design
- Rugged pull-through frame for durability
- Greaseless walking tandem and rolling basket bearings

Optional rear attachments include:

- Double formed hydraulically-positioned rolling basket breaks up clods and conditions the field
- Optional two-basket design for superior field conditioning
- Coil tine harrow - 3 bar

TRUE-TANDEM 345	22 Ft. (6.7 m)	25 Ft. (7.6 m)	28 Ft. (8.5 m)	31 Ft. (9.4 m)	34 Ft. (10.4 m)
TRACTOR REQUIREMENTS					
PTO Horsepower	152–222 hp (114–165 kw)	173–250 hp (129–186 kw)	192–279 hp (143–208 kw)	212–307 hp (158–229 kw)	231–336 hp (173–250 kw)
Hydraulics	Four hydraulic remote valves				
Operating Depth	2–4 in. (51–102 mm)				
FRAME					
Main Frame	6×6 in. (152×152 mm) and 4×4 in. (102×102 mm) fore-aft tubes				6×8 in. (152×204 mm) and 4×4 in. (102×102 mm) fore-aft tubes
Wing Frame - single fold	6×6 in. (152×152 mm) and 4×6 in. (102×152 mm) fore-aft tubes. Cushioned or rigid gangs; heavy cast 4.5" diameter spools; flattened blade centers for a tight fit				6×6 in. (152×152 mm) fore-aft tubes
Gang Frame	3×5 in. (76×127 mm) rectangular tube. Cushioned or rigid gangs; heavy cast 4.5" diameter spools; flattened blade centers for a tight fit				
Gang Angle	18 degrees front and rear				
WHEELS AND TIRES					
Main Frame	8-bolt, 12.5×15 FI			380/60 R16.5	380/60 R16.5
Wing Frame	6-bolt, 11L×15 8-ply standard, 8-bolt w/ stubble resistant tires optional				
Gauge Wheels	Pivoting wing stabilizer 6-bolt, 7.60×15 8-ply				
ARBOR BOLT					
Size & Torque	1.5 in. (38 mm), round spring steel torqued to 800 lb-ft. (1085 Nm)				
BLADES AND BEARINGS					
Spacing	7.5 in. (191 mm) or 9 in. (229 mm)				
Blades	Earth Metal® blades for long-lasting durability. Blade diameter: 22 in. (559 mm); Gang mounts: rigid cushion				
Number of Blades - 9 in. (229 mm) spacing	62	70	78	86	94
Tillage Width - 9 in. (229 mm) blade spacing	22 ft. 2 in. (6.8 m)	25 ft. (7.6 m)	27 ft. 10 in. (8.5 m)	30 ft. 8 in (9.4 m)	33 ft. 7 in. (10.2 m)
SCRAPERS					
	Heavy-duty spring steel rigid standard				
TRANSPORT SIZE (WITH NO HARROW)					
Transport Width	15 ft. 2 in. (4.6 m)		17 ft. 0 in. (5.2 m)		18 ft. 0 in. (5.5 m)
Transport Height	10 ft. 0 in. (3.0 m)	11 ft. 2 in. (3.4 m)	11 ft. 7 in. (3.5 m)	12 ft. 8 in. (3.9 m)	14 ft. 4 in. (4.4 m)

Specifications are subject to change without notice.

CNH America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

©2014 CNH America LLC. All rights reserved. Case IH and Earth Metal are registered trademarks of CNH America LLC. Printed in U.S.A. www.caseih.com

CIH01051401