

NEW! BOOMER™ CVT COMPACT TRACTORS

BOOMER™ 45D | BOOMER™ 50D

PRELIMINARY (CANADA)



If you're ready to work with greater power, comfort and ease, the deluxe Boomer 45D and Boomer 50D are exactly what you've been looking for.

CLEAN-RUNNING EFFICIENT ENGINES

These new Boomer tractors are powered by four-cylinder, naturally aspirated, proven 45- and 50-HP Shibaura engines.

UPGRADE TO THE SUITE

The factory-installed SuperSuite™ cab is, by far, the most spacious and comfortable compact tractor cab on the market. Because of standard heat and air conditioning, you can work in all-day comfort, protected from weather, insects, dust, and noise. For easy storage, the cab clears a standard 8-foot garage opening.

SPACIOUSNESS COMES STANDARD

The SuperSuite cab is the biggest cab in its class. You'll find the hip room, legroom, and headroom to be generous, to say the least, with 60 cubic feet of interior space surrounding you. Two large doors with grab rails open on gas struts to wide 16.5-inch entry thresholds for easy entrance and exit on either side.

VISIBILITY COMES FIRST

You will instantly see the difference 48.6 square feet of glass makes. It adds up to 360° visibility that cannot be matched in any other compact tractor cab. The sloped hood gives you excellent forward visibility from the tractor seat. That's because the muffler is under the hood and not in your line of sight like competitive tractors. Add the sloped-arm New Holland 250TLA loader and you get a clear line of sight to the bucket

edges. A standard high-visibility roof panel allows you to see a loader through its full range of operation for safe, efficient and fatigue-free operation.

THE MOST STANDARD FEATURES

Convenience and comfort are part of the design of Boomer 45D and Boomer 50D tractors. You get a long list of deluxe features -- and all are standard equipment, including tilting/telescoping steering wheel, exterior and interior mirrors, a deluxe three-point hitch and much more. Check the full listing on the back.

INDUSTRY-LEADING CVT

The Boomer EasyDrive™ Continuously Variable Transmission (CVT) is the best in the business because it adapts easily to varying conditions. It drives just like a car using a single "go" pedal. The transmission automatically adjusts to deliver the desired speed and matches load conditions. Change directions using the convenient shuttle lever to the left of the steering wheel.

ADDITIONAL EASYDRIVE™ ADVANTAGES

The EasyDrive CVT gets the job done efficiently, so whatever you're doing feels less like work and more like fun. This innovative transmission offers an automotive-style cruise control, allowing you to hold, fine-tune, or resume working speeds. A response setting allows operator to adjust the acceleration and deceleration characteristics of the tractor to suit their driving style or application. In slippery conditions, just engage four-wheel drive electronically with the flip of a switch. With a speed range up to 18.6 mph, you are sure to get all the chores done fast.

BOOMER™ CVT COMPACT TRACTOR SPECIFICATIONS – PRELIMINARY

		BOOMER™ 45D	BOOMER™ 50D
Engine			
Model		N844L	N844L
Gross HP @ rated speed		45 @ 2600 rpm	50 @ 2800 rpm
PTO HP @ rated speed		36.0 @ 2600 rpm	40.0 @ 2800 rpm
No. of cylinders		4	4
Displacement	cu. in. (L)	135.2 (2.2)	135.2 (2.2)
Fuel tank capacity	US gal. (L)	13 (49.2)	13 (49.2)
Alternator	amps	75	75
Transmission			
Transmission type		EasyDrive™ Continuously Variable Transmission (CVT)	
Controls		Single foot pedal and shuttle lever	
Number of forward speeds	mph (km/h)	Infinite up to 18.6 (30)	
PTO			
Type		Independent	Independent
Standard Rear	rpm	540	540
Optional Mid	rpm	2000	2000
Hydraulics			
Implement pump flow	GPM (L/min)	9.8 (37.1)	9.8 (37.1)
Steering pump flow	GPM (L/min)	5.1 (19.4)	5.1 (19.4)
3 Point Hitch			
Hitch type		Category I	Category I
Lift capacity @ 24" behind link ends	lbs. (kg)	2800 (1270)	2800 (1270)
Axle Options			
Four Wheel Drive (FWD)		Standard	Standard
Dimensions (Standard FWD, R4 tires)			
Wheelbase	in. (mm)	73.5 (1867)	73.5 (1867)
Overall length with 3-point hitch horizontal	in. (mm)	122 (3099)	122 (3099)
Minimum overall width @ rear axle	in. (mm)	68.3 (1735)	68.3 (1735)
Height to top of cab	in. (mm)	90.3 (2294)	90.3 (2294)
Ground clearance - drawbar	in. (mm)	12.3 (313)	12.3 (313)
Approximate ship weight	lbs. (kg)	4136 (1876)	4136 (1876)

Additional Standard Equipment (Cab):

- 2 wide-opening doors with grab rails and gas strut assist
- Tilt and telescopic steering column
- Deluxe cloth covered seat with weight adjustable suspension and swivel
- Interior rearview mirror
- Suspended brake pedals
- 12V power outlet and accessory power socket
- Adjustable sun visor
- Single cab air filter
- Left and right side steps
- Removable plug in rear of cab to route harness
- Cup holder
- Toolbox
- Flexible link-ends
- Telescoping stabilizers
- High-visibility roof panel
- Heat and air conditioning
- Radio-ready with antenna and speakers
- Dual external mirrors
- Front and rear cab-mounted work lights
- Front windshield washer/wiper

MAINTENANCE MEETS CONVENIENCE

Maintaining a Boomer compact tractor is easy because all routine maintenance points are located on the right side of the engine. In addition, you can easily check engine oil level without raising the hood and without removing the loader.

ACCESS DOESN'T GET ANY EASIER

For easy access to the engine, radiator, air cleaner, power steering reservoir, and battery, simply open the hood. It raises and pivots forward, allowing for access even when a loader or front blade is attached.



New Holland offers a full line of loaders and implements to match the Boomer 45D and Boomer 50D. **Ask your dealer today.**

WARRANTY

Full coverage: 24 months or 2,000 hours. **Powertrain:** 36 months or 200 hours.

*Extended warranty available



Learn more at www.newholland.com/na

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.

© 2014 CNH Industrial America LLC. All rights reserved. New Holland is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Any trademarks referred to herein, in association with goods and/or services of companies, other than owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates, are the property of those respective companies.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.