

SPECIFICATIONS	SB531	SB541
BALE SIZE		
Cross Section	356 x 457 mm (14 x 18 in.)	356 x 457 mm (14 x 18 in.)
Length	305 to 1321 mm (12 to 52 in.)	305 to 1321 mm (12 to 52 in.)
Density Control	Hydraulic bale tension	Hydraulic bale tension
PICKUP		
Width	1650 mm (65 in.)	1900 mm (75 in.)
No of bars in Pickup	5 bars (110 teeth)	6 bars (156 teeth)
Windguard	Std - 8 fingers	Std - 13 fingers
Raise	Manual	Hydraulic lift
FEEDER		
Type	Packer fork with 2 paired rotating fingers	Packer fork with 3 paired rotating fingers
Opening	0.182 m² (283 in.²)	0.182 m ² (283 in. ²)
PLUNGER		
Speed	93 strokes/min	93 strokes/min
Stroke	762 mm (30 in.)	762 mm (30 in.)
TYING MECHANISM		
Туре	Twine knotter	Twine knotter
Drive Mechanism	Gear & Shaft	Gear & Shaft
Protection	Shear bolt	Shear bolt
Twine capacity	6 balls	8 balls
MAIN DRIVE		
PTO type	3 joint, ASABE HD Category 6	3 joint, ASABE HD Category 6
PTO protection	Slip Clutch + overrunning clutch	Slip Clutch + overrunning clutch
Flywheel diameter	559 mm (22 in.)	559 mm (22 in.)
Flywheel weight	113 kg (250 lb)	113 kg (250 lb)
TRACTOR REQUIREMENT		
Minimum PTO hp	45 kW (61 hp)	56 kW (76 hp)
Hyd remotes	0	2 (pick-up lift & tongue swing)
DIMENSIONS		
Overall Width	2794 mm (110 in.)	3048 mm (120 in.)
Overall Length (no bale chute)	1778 mm (70 in.)	1797 mm (70.75 in.)
Weight	1542 kg (3400 lb)	1685 kg (3715 lb)
Tyres (Left/Right)	31 x 13.50 - 15 6PR / 27 x 9.50 - 15 6PR	31 x 13.50 - 15 6PR / 27 x 9.50 - 15 6PR



SAFETY NEVER HURTS![™] Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial Australia Pty Ltd reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used. ©2018 CNH Industrial Australia Pty Ltd. All rights reserved. Case IH, its respective logos and the red, black and grey color scheme, as well as corporate and product identity used herein, are trademarks of CNH Industrial N.V. and may not be used without permission. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Printed in Australia. www.caseih.com 18APACAUSSSB001

