

NUTRI-PLACER 930 PULL-TYPE APPLICATOR SPECIFICATIONS

CASE IH
AGRICULTURE



NUTRI-PLACER 930 PULL-TYPE APPLICATOR

Features

- Heavy-duty frame for increased in toolbar strength
- 3-section flex for ground contouring
- All new rear hitch for simple, reliable hook-up
- 38 cm, 51 cm, 76 cm (15-, 20-, & 30-inch) row spacing
- Hydraulic single point depth control
- Easy leveling turnbuckles for wing wheel adjustments – double fold units
- Reduced service requirements
- Proven, ground-engaging components for NH₃ placement
- Independent pivoting coulters
- High-clearance shank assemblies have adjustable trip pressure
- High, under-frame clearance
- Choose the shank that's right for your operation
- Standard stubble-resistant tires



NUTRI-PLACER 930 PULL-TYPE APPLICATOR	8.4 M (27.5 FT)	9.9 M (32.5 FT)	11.4 M (37.5 FT)	12.2 M (42.5 FT)	14.5 M (47.5 FT)
Frame Style	Pull-Type				
Row Spacing	38 cm (15 in.), 51 cm (20 in.), 76 cm (30 in.)				
Main Frame & Wing Tubing	10 cm x 15 cm Double-Rank (4 in. x 6 in.)				
Pull Frame	A-Frame 10.1 cm x 25.4 cm Tubes (4 in. x 10 in.)				
Fold Type	Single Fold			Double Fold	
Transport Height	3.2 m (10 ft. 6 in.)	3.7 m (12 ft. 4 in.)	4.2 m (13 ft. 10 in.)	4.1 m (13 ft. 6 in.)	
Transport Width	5.1 m (16 ft. 10 in.)			5.6 m (18 ft. 6 in.)	
Main Transport Wheels	Singles Qty. 2 – 12.5L x 15 Stubble-Resistant FI Tires with 8-Bolt Hubs (Optional Walking Tandem Qty. 4 – 11L x 15 Stubble-Resistant FI Tires with 8-Bolt Hubs)				Walking Tandem Qty. 4 – 12.5L x 15 Stubble-Resistant FI Tires with 8-Bolt Hubs
Wing Wheels	Single Qty. 2 – 9.5L x 15 Stubble-Resistant FI Tires with 6-Bolt Hubs (Optional Walking Tandem Qty. 4 – 9.5L x 15 Stubble-Resistant FI Tires with 6-Bolt Hubs)				Walking Tandem Qty. 4 – 9.5L x 15 Stubble-Resistant FI Tires with 6-Bolt Hubs
Outer Gauge Wheel	None				Pin Adjust Qty. 2 – 9.5L x 15 Stubble-Resistant FI Tires
Hitch	Category 3 Clevis		Category 3 Clevis (Opt. Cat. 4)	Category 4 Clevis (Opt. Cat 5)	
Wing Flex	3 Section Flex (7° Down & 16° Up)				
HP Requirement	165 – 220 Engine HP	195 – 260 Engine HP	225 – 300 Engine HP	255 – 340 Engine HP	285 – 380 Engine HP
Operating Speed	8 – 11.3 kph (5 – 7 mph)				
Depth Adjustment	Single-Point Hydraulic				
Wheel Pivot Lubrication	Composite Self-Lubricating Bushing				
Hinge Lubrication	Composite Self-Lubricating Bushing				
Shank Options	Rigid Mtd., HD Spring Mtd., Rigid CS, HD Spring CS, or High Clearance Shank (HCS)				
Coulter Options	51 cm (20 in.) Coulters, 61 cm (24 in.) Coulters				
Sealer Options	36 cm (14 in.) Spring Double Disk, 46 cm (18 in.) Spring Double Disk-Notched, 46 cm (18 in.) Spring Double Disk-Dull				
NH ₃ Rear Hose Boom	Optional Single or Double				
Rear Hitch	Optional Constant Level Rear Hitch 11 340 kg (25,000 lbs.) Towing Capacity				



INTERNATIONAL



SAFETY NEVER HURTS!™ Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided.

This literature has been published for worldwide circulation. The standard and optional equipment and the availability of individual models may vary from one country to the next. Case IH reserves the right to undertake modifications without prior notice to the design and technical equipment at all times without this resulting in any obligation whatsoever to make such modifications to units already sold. Whilst every effort is made to ensure that the specifications, descriptions and illustrations in this brochure are correct at the time of going to press, these are also subject to change without prior notice. Illustrations may show optional equipment or may not show all standard equipment.

CNH International S.A. - Network Development & Advertising - Riva Paradiso, 14 - 6902 Paradiso-Lugano Switzerland

© 2012 CASE IH - Visit our website: www.caseih.com - Send us an e-mail: international@caseih.com

Published by CNH INTERNATIONAL SA. Communications & Advertising - Printed in Italy - 07/12 - Cod. N. IR2409C/INB

Your Case IH Dealer