

NUTRI-PLACER 940 PULL-TYPE APPLICATOR SPECIFICATIONS



CASE IH NUTRI-PLACER 940 PULL-TYPE APPLICATOR

Features

- 7-section fold, 5-section flex frame for ground contouring
- High, under-frame clearance for residue flow
- Heavy-duty running gear
- 23% increase in width
- Matched capacity to largest tractors in the industry
- Compatible with commodity air systems
- Slim design for narrow transport; excellent roading
- Proven, ground-engaging components for NH_3 retention
- Hydraulic, single-point depth control
- Independent, pivoting coulters
- High-clearance shank with adjustable holding power
- 38 cm, 76 cm (15- and 30-inch) row spacing
- All new rear hitch for simple, reliable hook-up
- Easy leveling turnbuckles for fore/aft pitch and wing wheel adjustment
- Reduced service requirements
- Heavy frame tube



NUTRI-PLACER 940 PULL-TYPE APPLICATOR	15.2 M (50 FT.)	18.3 M (60 FT.)	19.8 M (65 FT.)
Frame Style	Pull-Type		
Standard Shank Configuration	20 Shank HCS on 762 mm (30 in.) Centers with Optional 610 mm (24 in.) Coulters	24 Shank HCS on 762 mm (30 in.) Centers with Optional 610 mm (24 in.) Coulters	26 Shank HCS on 762 mm (30 in.) Centers with Optional 610 mm (24 in.) Coulters
Optional Shank Configuration	N/A	47 Shank HCS on 381 mm (15 in.) Centers with No Coulters	51 Shank HCS on 381 mm (15 in.) Centers with No Coulters
Transport Height	4.2 m (13 ft. 9 in.)		
Transport Width	5.7 m (18 ft. 9 in.)		
Main Transport Wheels	Walking Tandem 4x16.5 – 16.1 14 ply (Optional Stubble-Resistant FI Tires with 8-Bolt Hubs)		
Wing Wheels	Walking Tandem 8x12.5L – 15 10 ply (Optional Stubble-Resistant FI Tires with 6-Bolt Hubs)		
Outer Gauge Wheel	None		Pin Adjust 2x20.5 – 8 Load Range D
Weight	9752 kg (21,150 lb.)	10 206 kg (22,500 lb.)	10 433 kg (23,000 lb.)
Configuration	5-Section Flex, 5-Section Fold	5-Section Flex, 7-Section Fold (Fold Forward Outer Wing)	
HP Requirement	300 – 460 Engine HP	360 – 550 Engine HP	390 – 598 Engine HP
Knife Options	All Side Mounted		
Operating Speed	8 – 12.9 kph (5 – 8 mph)		
Depth Adjustment	Single-Point Hydraulic		
Hinge Lubrication	Composite Self-Lubricating Bushing		
Options	Constant Level Rear Hitch, 61 cm (24 in.) Coulters, 46 cm (18 in.) Dull or Notched Sealing Discs, Rear Cooler Mounting Bracket Kit		



INTERNATIONAL

SAFETY NEVER HURTS!™ Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided.

This literature has been published for worldwide circulation. The standard and optional equipment and the availability of individual models may vary from one country to the next. Case IH reserves the right to undertake modifications without prior notice to the design and technical equipment at all times without this resulting in any obligation whatsoever to make such modifications to units already sold. Whilst every effort is made to ensure that the specifications, descriptions and illustrations in this brochure are correct at the time of going to press, these are also subject to change without prior notice. Illustrations may show optional equipment or may not show all standard equipment.

CNH International S.A. - Network Development & Advertising - Riva Paradiso, 14 - 6902 Paradiso-Lugano Switzerland

© 2012 CASE IH - Visit our website: www.caseih.com - Send us an e-mail: international@caseih.com

Published by CNH INTERNATIONAL SA. Communications & Advertising - Printed in Italy - 07/12 - Cod. N. IR2410C/INB

Your Case IH Dealer