

# NUTRI-TILLER 950 STRIP-TILL SYSTEM SPECIFICATIONS

**CASE IH**  
AGRICULTURE





# CASE IH NUTRI-TILLER 950 STRIP-TILL SYSTEM

## Features

- 3- & 5-section flex frame for ground contouring
- High, under-frame clearance for residue flow
- Heavy-duty running gear
- Matched capacity to largest tractors in the industry

- Slim, yet stable design for narrow transport and excellent roading
- Proven, ground-engaging components for product retention
- Hydraulic, single-point depth control
- Independent, pivoting coulters
- Reduced service requirements

- High-clearance shank with adjustable holding power
- 76 cm (30-inch) row spacing
- New, heavy-duty rear hitch for pulling tanks; simple, reliable hook-up
- Easy-leveling turnbuckles for fore/aft pitch and wing wheel adjustment



- Big widths for high productivity
- Heavy-duty frame
- Standard, stubble-resistant (FI) tires
- Compatible with commodity air systems

NUTRI-TILLER 950 STRIP-TILL SYSTEM	8-ROW	12-ROW	16-ROW	24-ROW
Frame Style	Pull-Type			
Working Width [76 cm (30 in.) centers]	6.1 m (20 ft.)	9.1 m (30 ft.)	12.2 m (40 ft.)	18.3 m (60 ft.)
Main Frame & Wing Tubing	10 cm x 15 cm Double-Rank (4 in. x 6 in.)			15 cm x 15 cm Triple-Rank (6 in. x 6 in.)
Pull Frame	A-Frame 10.1 cm x 25.4 cm Tubes (4 in. x 10 in.)			“T-Bone” Pull Hitch, 15.2 cm x 25.4 cm x 1.3 cm Wall (6 in. x 10 in. X 1/2 in.)
Fold Type	Single Fold		Double Fold	Triple Fold (Fold Forward Outer Wings)
Transport Height	2.6 m (8 ft. 6 in.)	4.1 m (13 ft. 6 in.)		4.2 m (13 ft. 9 in.)
Transport Width	5.6 m (18 ft. 6 in.)	6 m (19 ft. 8 in.)	6 m (19 ft. 8 in.)	5.7 m (18 ft. 9 in.)
Main Transport Wheels	Walking Tandem Qty. 4 – 12.5L x 15 stubble-resistant FI Tires (8-Bolt Hubs)			Walking Tandem Qty. 4 – 16.5L x 16.1 Stubble-Resistant FI Tires (8-Bolt Hubs)
Wing Wheels	Walking Tandem Qty. 4 – 9.5L x 15 Stubble-Resistant FI Tires (6-Bolt Hubs)			Walking Tandem Qty. 8 – 12.5L x 15 Stubble-Resistant FI Tires (6-Bolt Hubs)
Hitch	Category 3 Clevis	Category 4 Clevis		Category 5 Clevis
Wing Flex	Rigid	3-Section Flex (7° Down & 16° Up)		5-Section Flex (Inner – 9° Down 20° Up; Outer – 7° Down, 7° Up)
Operating speed	8 – 11.3 kph (5 – 7 mph)			
HP Requirement	150 – 200 Engine HP	225 – 300 Engine HP	300 – 400 Engine HP	450 – 600 Engine HP
Shanks	HCS Spring Reset [Adjustable 386 kg (850 lbs.) or 567 kg (1,250 lbs.)]	HCS Spring Reset [Adjustable 386 kg (850 lbs.) or 567 kg (1,250 lbs.)] or Rigid 2.5 cm x 5 cm (1 in. x 2 in.) Shank		HCS Spring Reset [Adjustable 386 kg (850 lbs.) or 567 kg (1,250 lbs.)]
Depth Adjustment	Single-Point Hydraulic			
Hinge Lubrication	Composite Self-Lubricating Bushing			
Rear Hitch	Optional Constant Level Rear Hitch 11 340 kg (25,000 lbs.) Towing Capacity			
Options	61 cm (24 in.) Coulters			
	HCS Mount Row Cleaners			
	46 cm (18 in.) Berm Builders for HCS Shank			
	N/A	46 cm (18 in.) Disk Sealer for Rigid Shank		N/A
	Rear NH <sub>3</sub> Mounting Bracket Kit			
	Concave or Flat 36 cm (14 in.) Berm Conditioner Baskets			



INTERNATIONAL

**SAFETY NEVER HURTS!™** Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided.

This literature has been published for worldwide circulation. The standard and optional equipment and the availability of individual models may vary from one country to the next. Case IH reserves the right to undertake modifications without prior notice to the design and technical equipment at all times without this resulting in any obligation whatsoever to make such modifications to units already sold. Whilst every effort is made to ensure that the specifications, descriptions and illustrations in this brochure are correct at the time of going to press, these are also subject to change without prior notice. Illustrations may show optional equipment or may not show all standard equipment.

CNH International S.A. - Network Development & Advertising - Riva Paradiso, 14 - 6902 Paradiso-Lugano Switzerland

© 2012 CASE IH - Visit our website: [www.caseih.com](http://www.caseih.com) - Send us an e-mail: [international@caseih.com](mailto:international@caseih.com)

Published by CNH INTERNATIONAL SA. Communications & Advertising - Printed in Italy - 07/12 - Cod. N. IR2411C/INB

Your Case IH Dealer