

FARMALL® A SERIES TRACTORS

110 – 140 RATED HP

CASE II
AGRICULTURE



ONE MULTI-TASKER DESERVES ANOTHER.

You're doing it all – from field to feedlot – but you wouldn't be anywhere else, doing anything else. Case IH understands. That's why Case IH created the Farmall A series. These tractors are tough, reliable, remarkably versatile and an excellent value. The easy-to-use controls allow you to get in and go, and the comfortable operator environment makes a long day seem shorter. Not that you're in any hurry to go inside.



POWER & PERFORMANCE

POWER THROUGH EVERY CHORE.

Farmalls were not the first tractors on the farm, but they were the first to truly do every job around the farm. In the 1920's, Farmall tractors began to replace the farm's team of horses. That heritage is reinterpreted for today's needs in the Farmall A series. These tractors feature transmission, engine and hydraulic systems that work seamlessly to make complex chores easier and faster than ever. With eight models in 2WD and optional MFD configurations, they're the right size – for your operation and your budget.



ALL THE HORSEPOWER YOU NEED.

Farmall A series tractors are powered by one of two turbocharged engines: the 110A and 120A are equipped with a 4-cylinder (4.5 L) engine (shown above), while the 125A and 140A feature a 6-cylinder (6.7 L). Both are carefully tuned to provide fuel efficiency and a long engine life, with grid heaters for cold mornings.



SMOOTH SHIFTING OPTIONS.

Shift easily from forward to reverse with the standard 8x8 clutchless power shuttle, or choose the 8x8 Synchro mechanical option with mechanical reverser. For maximum control, choose the optional 16x8 power shuttle with hi-lo gear selection in every range. The controls are simple to use and ergonomically placed for easy operation.



BEST HITCH LIFT CAPACITY IN ITS CLASS.

Three-point hitch lift capacity is up to 4647 kg – with optional assist rams. Lift heavy loads with confidence thanks to the 84 lpm hydraulic flow capacity. Connect implements quickly and easily.

ENJOY THE VIEW.

Choose a Farmall A series ROPS tractor for an outstanding level of visibility and a lower base investment.



CLIMATE-CONTROLLED COMFORT.

Comfort doesn't have to break the bank. The Farmall A series cab platform keeps the elements out, while delivering the visibility you need to get the job done.

HAVE A SEAT.

An iso-mounted cab with a large operator platform helps reduce the impact of rough terrain and provide a more comfortable ride. Enjoy the standard contoured seat pictured here or opt for an air suspension seat.



COMFORT COMES STANDARD.

Hundreds of hours of research go into making long days seem shorter, controls seem more natural and chores seem less challenging in Case IH equipment. Farmall A series tractors continue the long-standing Farmall commitment, putting a high priority on operator comfort and productivity.

OPERATOR ENVIRONMENT


FARMALL A SERIES SERIES TRACTORS SPECIFICATIONS

Since 1923, the Farmall name has been synonymous with power, performance, durability and value. Case IH is proud to expand the Farmall A heritage with a new line of 110–140 HP tractors. These workhorse tractors provide value without compromise with many no-nonsense standard features, as-well-as factory options and dealer-installed options to create a tractor right for your operation at the right price.

| FARMALL A SPECIFICATIONS | FARMALL 110A | FARMALL 120A | FARMALL 125A | FARMALL 140A |
|---|---|---------------|---------------------|----------------|
| POWER | | | | |
| Type | Tier 3 | | | |
| Engine HP at 2,200 RPM | 110 | 118 | 125 | 140 |
| PTO HP at 1,900 RPM | 90 | 96 | 105 | 115 |
| Number of Valves | 8 | | 12 | |
| Aspiration | Turbocharged | | | |
| ELECTRICAL | | | | |
| Alternator Standard | 120 Amp | | | |
| Battery Standard | 12V-950 CCA | | | |
| TRANSMISSION/PTO | | | | |
| Standard (Base) | 8x8 synchronized mechanical shuttle w/ left hand shuttle | | | |
| Optional | 8x8 synchronized hydraulic shuttle w/ left hand shuttle | | | |
| Optional | 16x8 dual power synchronized hydraulic shuttle w/ left hand shuttle | | | |
| Creeper option | Available for all transmission | | | |
| PTO - Standard/Optional (with Two Individual Shafts) | 540 / 540 - 1,000 | | 540 - 1,000 / - | |
| AXLES | | | | |
| Standard/Rear Axle | Flange / Bar | | | |
| Bar Axle Diameter | 78 mm | | | |
| Rear Bar Axle Length | 2 489 mm | | | |
| Front Axle - Standard/Optional | 2WD / Class 3 Non-Suspended Standard-Duty | | | |
| Tread Adjustability | 1,626 – 2,032 mm | | | |
| Wheelbase Standard 2WD/MFD | 2,471 mm / 2,520 mm | | 2,667 mm / 2,642 mm | |
| HYDRAULICS/HITCH | | | | |
| System Type Standard | Fixed Displacement Pump (FD) | | | |
| Remotes - Standard/Optional | 1 Deluxe Remotes / 4 Deluxe Remotes | | | |
| Implement Flow Capacity - Standard/Optional | 49/83 L/min | | | |
| Steering/Secondary Pump Capacity | 34 L/min | | | |
| Tractor Hydraulic Total Flow Capacity - Standard/Optional | 83/132 L/min | | | |
| 3-Point Hitch Category | Cat II standard | | | |
| Lift capacity (OECD@610mm) standard / option 1 / option2 | 2,410 kg / 3,639 kg / 4,647kg | | | |
| CAPACITIES | | | | |
| Fuel Tank | 150 l | | 235 l | |
| Engine Oil with Filter | 11 l | | 14 l | |
| Hydraulic Fluid | 62 l | | | |
| CAB | | | | |
| Mounting | Iso-Mounted | | | |
| Seat - Standard/Optional | Mechanical / Air suspension | | | |
| WEIGHT | | | | |
| 2WD w / ROPS, lbs. (kgs) | 8,003 (3,630) | 8,091 (3,670) | 9,061 (4,110) | 9,061 (4,110) |
| MFD w / ROPS, lbs. (kgs) | 8,642 (3,920) | 8,818 (4,000) | 9,700 (4,400) | 9,700 (4,400) |
| 2WD w / cab, lbs. (kgs) | 8,708 (3,950) | 8,885 (4,030) | 9,766 (4,430) | 9,766 (4,430) |
| MFD w / cab, lbs. (kgs) | 9,348 (4,240) | 9,524 (4,320) | 10,406 (4,720) | 10,406 (4,720) |



¹FPT Industrial-engine ²ECE R-120 correspond to ISO TR14396

 Safety never hurts! Always read the Operator's Manual before working with any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. This literature has been published for worldwide circulation. The standard and optional equipment and the availability of individual models may vary from one country to the next. Case IH reserves the right to undertake modifications without prior notice to the design and technical equipment at all times without this resulting in any obligation whatsoever to units already sold. Whilst every effort is made to ensure that the specifications, descriptions and illustrations in this brochure are correct at the time of going to press, these are also subject to change without prior notice. Illustrations may show optional equipment or may not show all standard equipment. Case IH recommends **AKCELA** lubricants.

Case IH EMEA Brand Communications - Steyer Strasse 32, 4300, Sankt Valentin, Austria - © 2014 CASE IH - Visit our website: www.caseih.com
Send us an e-mail: Africa.MaxService@caseih.com - MiddleEast.MaxService@caseih.com - Farmall_A_Series_English - Cod. N. MEA14C0001