FARMALL® A SERIES TRACTORS 110 - 140 RATED HP CASELL

ONE MULTI-TASKER DESERVES ANOTHER.

You're doing it all – from field to feedlot – but you wouldn't be anywhere else, doing anything else. Case IH understands. That's why Case IH created the Farmall A series. These tractors are tough, reliable, remarkably versatile and an excellent value. The easy-to-use controls allow you to get in and go, and the comfortable operator environment makes a long day seem shorter. Not that you're in any hurry to go inside.







MODEL	CYLINDERS	RATED POWER (HP)	ASPIRATION
Farmall 110A	4	110	Turbocharged/Intercooled
Farmall 120A	4	118	Turbocharged/Intercooled
Farmall 125A	6	125	Turbocharged/Intercooled
Farmall 125A	6	140	Turbocharged/Intercooled

COMFORT COMES STANDARD.

Hundreds of hours of research go into making long days seem shorter, controls seem more natural and chores seem less challenging in Case IH equipment. Farmall A series tractors continue the long-standing Farmall commitment, putting a high priority on operator comfort and productivity.



ENJOY THE VIEW. Choose a Farmall A series ROPS tractor for an outstanding level of visibility and a lower base investment.



CLIMATE-CONTROLLED COMFORT.

Comfort doesn't have to break the bank.

The Farmall A series cab platform keeps the elements out, while delivering the visibility you need to get the job done. ------:



HAVE A SEAT.

An iso-mounted cab with a large operator platform helps reduce the impact of rough terrain and provide a more comfortable ride. Enjoy the standard contoured seat pictured here or opt for an air suspension seat.



POWERFUL ECONOMY.

Farmall A tractors are powered by fuel efficient turbocharged, intercooled engines that will work reliably in all conditions. The Farmall A will power efficiently through every task you give it, be it roadside mowing, loading, tilling or haying. These tough, versatile tractors will consistently deliver a flawless performance in the toughest conditions, keeping your costs down.

ALL THE HORSEPOWER YOU NEED.

The turbocharged FPT engines powering Farmall A tractors (4 cylinder, 4.5 I for the 110A and 120A; 6 cylinder, 6.7 I for the 125A and 140A) are carefully tuned for fuel efficiency and long life. The grid heaters will ensure they start reliably even in the coldest of mornings.



NON-STOP WORK.

With Farmall A tractors, you won't waste time refuelling. With the large fuel tank (150 litres for 4-cylinder and 235 litres for 6-cylinder models), you can work long days nonstop. And when you do need to refuel, it is a job quickly done, with the easily accessible side-mounted fuel tank under the operator platform.







4

ALL THE POWER YOU NEED.

Farmall A tractors deliver all the hydraulic flow you need to operate even power-hungry implements. The standard dual-pump, open-centre hydraulic system comes with 35 I implement pump. If even this is not enough, you can add a 35 I auxiliary pump to take care of steering and services, so that every ounce of power from the hydraulic system goes to your implement.





ALL THE REMOTE VALVES YOU NEED.

Farmall A tractors maximise their excellent versatility with a choice of remote valves. The hydraulic flow to the implement is managed by the two standard closed-centre deluxe rear remote valves with flow control and adjustable detent. You can add four closed-centre, deluxe rear remotes to run multiple hydraulic operations simultaneously. You can control them all comfortably from your seat. Hook-up and operation is intuitive with the colour coded levers that correspond to the color of the remote valves.



CHAMPION WEIGHTLIFTER.

Productivity soars with the best-in-class hitch lift capacity and all the remote valves you need to change implements easily and quickly. The powerful three-point hitch delivers 23 percent more than competitive tractors in the same class as the Farmall A. The two standard deluxe remote valves with flow control and breakaway couplers can easily be supplemented with two more remotes if needed.



MULTI-TASK LIKE A PRO.

Haying, loading, blading, feeding the cattle and horses. It all needs to be done. Your Case IH dealer will work with you to choose the best options and attachments for your new Farmall A series tractor so you can check tasks off your list quickly and efficiently.

LOADERS FIT FOR EVERY TASK.

Farmall A tractors can be offered loader-ready, by including an integrated park stand, new joystick and compact, protected bucket level indicator. An increased bucket roll back angle on mechanical self-leveling loaders provides additional leveling capabilities and helps eliminate spillage. A new Multi-Coupler design features flat-faced, no-spill couplers with electrical quick connect. The new Multi-Coupler tool makes it easy to connect all the hydraulics to your loader in one simple operation. It eliminates problems with incorrect connections, pressure in the hoses or oil leaks. The Lock & Go automatic quick coupling system lets you install and remove the loader with minimum effort, no loose parts and no tools.

MORE THAN TRACTORS TO WORK FOR YOU: WE'VE GOT PEOPLE TO WORK WITH YOU.

When you buy a Case IH machine, you can be sure not only that you're buying the best product, but also that you've got the best dealer back-up behind you. Case IH dealers can offer advice on selecting the right machine, will ensure they deliver what you need when you need it, and will then continue to back you and your equipment with the service and spare parts backing you'd expect from a name as trusted as Case IH.



SKILLED BUSINESS ADVISOR AT YOUR DEALERSHIP. DEMAND MORE FROM YOUR CASE IH DEALERSHIP.

Purchasing a standalone piece of new equipment? Keeping a whole fleet up-to-date? Whatever your size of operation, contact your local Case IH dealership for professional advice on your business needs. Case IH knows your farming needs best.



MAINTAIN THE PRODUCTIVITY OF YOUR INVESTMENT.

Case IH and its dedicated dealer network provide excellent support when you take delivery of your new machine and whilst it remains in your ownership. On the farm, you can rely on trained service professionals to maintain the productivity of your investment.



DO NOT RISK YOUR MACHINE'S LIFE. BUY CNH INDUSTRIAL PARTS & SERVICE!

Protect the value of your investment. Behind every Case IH product stands an extensive parts logistics organisation, stocking parts for products both old and new. Choosing to fit genuine Case IH parts will maintain the safety, value and performance of your original investment.



FARMALL A SERIES SERIES TRACTORS SPECIFICATIONS

Since 1923, the Farmall name has been synonymous with power, performance, durability and value. Case IH is proud to expand the Farmall A heritage with a new line of 110–140 HP tractors. These workhorse tractors provide value without compromise with many no-nonsense standard features, as-well-as factory options and dealer-installed options to create a tractor right for your operation at the right price.

FARMALL A SPECIFICATIONS	FARMALL 110A	FARMALL 120A	FARMALL 125A	FARMALL 140A			
POWER							
Туре		Tier 3					
Engine HP at 2,200 RPM	110	118	125	140			
PTO HP at 1,900 RPM	95	98	105	117			
Number of Valves		8	1	2			
Aspiration		Turbocharged					
ELECTRICAL							
Alternator Standard		120 Amp					
Battery Standard		12V-950 CCA					
TRANSMISSION/PTO		221 000 0011					
Standard (Base)		8x8 synchronized mechanical shuttle w/ left hand shuttle					
Optional		8x8 synchronized hydraulic shuttle w/ left hand shuttle					
Optional		16x8 dual power synchronized hydraulic shuttle w/ left hand shuttle					
Creeper option		Available for all transmission					
PTO - Standard/Optional (with Two Individual Shafts)	540 / 5	40 - 1,000	540 - 1,000 / -				
AXLES		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		,			
Standard / Rear Axle		Flange / Bar					
Bar Axle Diameter		78 mm					
Rear Bar Axle Length		2 489 mm					
Front Axle - Standard/Optional		2WD / Class 3 Non-Suspended Standard-Duty					
Tread Adjustability		1.626 – 2.032 mm					
Wheelbase Standard 2WD/MFD	2.570 mm	2.570 mm / 2.520 mm 2.667 mm / 2.642 mm					
HYDRAULICS/HITCH				F-			
System Type Standard		Fixed Displacement Pump (FD)					
Remotes - Standard/Optional		1 Deluxe Remotes / 4 Deluxe Remotes					
Implement Flow Capacity - Standard/Optional		49/84 Umin					
Steering/Secondary Pump Capacity		30 L/min					
Tractor Hydraulic Total Flow Capacity - Standard/Optional		83/132 L/min					
3-Point Hitch Category		Cat II standard					
Lift capacity (OECD@610mm) standard / option 1 / option2		2,410 kg / 3,639 kg / 4,647kg					
CAPACITIES		, ,					
Fuel Tank	1	501	235 I				
Engine Oil with Filter		111	14				
Hydraulic Fluid		621					
CAB							
Mounting		Iso-Mounted					
Seat - Standard/Optional		Mechanical / Air suspension					
WEIGHT							
2WD w / ROPS, lbs. (kgs)	8,003 (3,630)	8,091 (3,670)	9,061 (4,110)	9,061 (4,110)			
MFD w / ROPS, lbs. (kgs)	8,642 (3,920)	8,818 (4,000)	9,700 (4,400)	9,700 (4,400)			
2WD w / cab, lbs. (kgs)	8,708 (3,950)	8,885 (4,030)	9,766 (4,430)	9,766 (4,430)			
MFD w / cab, lbs. (kgs)	9,348 (4,240)	9,524 (4,320)	10,406 (4,720)	10,406 (4,720)			

