



FARMALL JXM

TRACTORS 80 - 90 HP



| SPECIFICATIONS | FARMALL JXM 80 | FARMALL JXM 90 |
|--|--|----------------|
| ENGINE | | |
| Model | S8000 | |
| Emission | Tier III | |
| No. of cylinders/ aspiration | 4 / Turbocharged Aftercooled | |
| Capacity/Bore x stroke(cm ³) / (mm) | 3908 / 104 x 115 | |
| Engine rated power @ 2300 rpm (kW/hp) | 59.7 / 80 | 67.2 / 90 |
| Maximum torque at 1400 rpm (Nm) | 310 | 340 |
| Fuel tank capacity (L) | 90 | |
| TRANSMISSION | | |
| Transmission Type | Synchromesh gears + Power Shuttle | |
| Clutch Type | Mechanical Double clutch / Power Shuttle main clutch & Mechanical PTO clutch | |
| No of Gears | 12F+12R | |
| Optional Speeds | 8F+8R,12F+12R Creeper, 20F+20R Creeper | |
| PTO | | |
| Standard | 540 | |
| Optional | 540/540E & 540/1000 | |
| Type | Reversible / Ground Speed | |
| HYDRAULICS | | |
| Draft sensing | Top Link | |
| Rear linkage category | I-II | |
| Stabiliser & Link ends | Chain - Fixed / Telescopic - Flexible | |
| Mechanical lift control | Position, draft, mixed / Fast Raise-Lower | |
| Main pump flow – standard (l/min) | 54, 60 (Opt) | |
| Steering pump flow (l/min) | 26 / 31 | |
| Maximum number of remote valves | 3 | |
| Maximum lift capacity at ball ends with arms horizontal (kg) | 2500 | |
| AXLES | | |
| Front | 2 / 4 WD | |
| Rear | Heavy Duty straight axle | |
| DIMENSIONS & WEIGHT | | |
| Wheel Base 2WD (mm) | 2283 | |
| Wheel Base 4WD (mm) | 2258 | |
| Total Weight 2WD (kg) | 2825 | |
| Total Weight 4WD (kg) | 3085 | |

 **SAFETY NEVER HURTS!™** Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. This literature has been published for worldwide circulation. The standard and optional equipment and the availability of individual models may vary from one country to the next. Case IH reserves the right to undertake modifications without prior notice to the design and technical equipment at all times without this resulting in any obligation whatsoever to make such modifications to units already sold. Whilst every effort is made to ensure that the specifications, descriptions and illustrations in this brochure are correct at the time of going to press, these are also subject to change without prior notice. Illustrations may show optional equipment or may not show all standard equipment. Case IH recommends **AKCELA** lubricants. CNH International Asia, Middle East and Africa - Riva Paradiso, 14 - 6902 Paradiso-Lugano Switzerland - Visit our website: www.caseih.com - Case IH Farmall JXM Brochure 08/20 AMEA - 20AMEAMEAJXM001

