

Cummins (Cummins Filtration)

Chemwatch: 4612-14 Version No: 3.1.1.1 Material Safety Data Sheet according to NOHSC and ADG requirements Chemwatch Hazard Alert Code: 2

Issue Date: 01/01/2013 Print Date: 06/11/2014 Initial Date: Not Available S.Local.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	New Holland NH Premix 50
Chemical Name	Not Applicable
Synonyms	NH Premix 50, NHCOOLANT208L - 208 Ltr, NHCOOLANT20L - 20 Ltr,, Part No: NHCOOLANT05L - 5Ltr,, inhibited ethylene glycol base antifreeze coolant
Proper shipping name	Not Applicable
Chemical formula	Not Applicable
Other means of identification	Not Available
CAS number	Not Applicable

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified

Ready to use inhibited engine coolant and antifreeze.

Details of the manufacturer/importer

Registered company name	Cummins (Cummins Filtration)	New Holland
Address	31 Garden Street Kilsyth 3137 VIC Australia	31-53 Kurrajong Road St Mary's 2760 NSW Australia
Telephone	+61 3 9721 9100	+61 2 9673 7777
Fax	+61 3 9721 9148	+61 2 9673 4588
Website	Not Available	Not Available
Email	Not Available	Not Available

Emergency telephone number

Association / Organisation	Not Available	Not Available
Emergency telephone numbers	1800 039 008 (24 hours)	Not Available
Other emergency telephone numbers	+61 3 9573 3112	Not Available

CHEMWATCH EMERGENCY RESPONSE

Primary Number	Alternative Number 1	Alternative Number 2
1800 039 008	+612 9186 1132	Not Available

Once connected and if the message is not in your prefered language then please dial 01

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

CHEMWATCH HAZARD RATINGS

	Min	Max	
Flammability	0		
Toxicity	2		0 = Minimum
Body Contact	2		1 = Low
Reactivity	0	1	2 = Moderate 3 = High
Chronic	2		4 = Extreme

Poisons Schedule	S5	
	R22	Harmful if swallowed.
	R68(3)	Possible risk of irreversible effects.
Risk Phrases ^[1]	R40(3)	Limited evidence of a carcinogenic effect.
	R33	Danger of cumulative effects.
	R52	Harmful to aquatic organisms.
Legend:	1. Classified by (Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex



Relevant risk statements are found in section 2

Indication(s) of danger	Xn
SAFETY ADVICE	
S13	Keep away from food, drink and animal feeding stuffs.
S23	Do not breathe gas/fumes/vapour/spray.
S29	Do not empty into drains.
S35	This material and its container must be disposed of in a safe way.
S36	Wear suitable protective clothing.
S37	Wear suitable gloves.
S40	To clean the floor and all objects contaminated by this material, use water.
S46	If swallowed, seek medical advice immediately and show this container or label.
S53	Avoid exposure - obtain special instructions before use.
S56	Dispose of this material and its container at hazardous or special waste collection point.
S57	Use appropriate container to avoid environmental contamination.

Other hazards

May produce discomfort of the eyes and skin*.
Inhalation may produce health damage*.
May affect fertility*.
May be harmful to the foetus/ embryo*.
Vapours potentially cause drowsiness and dizziness*.
Repeated exposure potentially causes skin dryness and cracking*.
Possible skin sensitizer*.
HARMFUL-May cause lung damage if swallowed.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
107-21-1	30-60	ethylene glycol

Chemwatch: 4612-14		Page 3 of 11	Issue Date: 01/01/2013
Version No: 3.1.1.1		New Holland NH Premix 50	Print Date: 06/11/2014
Not Available	2	concentrate corrosion inhibitor	
Not Available	NotSpec.	contains minor amounts of	
Not Available	NotSpec.	potassium phosphate as	
7778-77-0	NotSpec.	potassium phosphate, monobasic	
7632-00-0	NotSpec.	sodium nitrite	
7631-99-4	NotSpec.	sodium nitrate	
7631-95-0	NotSpec.	sodium molybdate	
Not Available	NotSpec.	sodium silicate as	
10213-79-3	NotSpec.	sodium metasilicate, pentahydrate	
7732-18-5	30-60	water	

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	 If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

For acute or short term repeated exposures to ethylene glycol:

- Early treatment of ingestion is important. Ensure emesis is satisfactory.
- Test and correct for metabolic acidosis and hypocalcaemia.
- Apply sustained diuresis when possible with hypertonic mannitol.
- Evaluate renal status and begin haemodialysis if indicated. [I.L.O]
- Rapid absorption is an indication that emesis or lavage is effective only in the first few hours. Cathartics and charcoal are generally not effective.
- Correct acidosis, fluid/electrolyte balance and respiratory depression in the usual manner. Systemic acidosis (below 7.2) can be treated with intravenous sodium bicarbonate solution.
- Ethanol therapy prolongs the half-life of ethylene glycol and reduces the formation of toxic metabolites.
- Pyridoxine and thiamine are cofactors for ethylene glycol metabolism and should be given (50 to 100 mg respectively) intramuscularly, four times per day for 2 days.
- Magnesium is also a cofactor and should be replenished. The status of 4-methylpyrazole, in the treatment regime, is still uncertain. For clearance of the material and its metabolites, haemodialysis is much superior to peritoneal dialysis.

[Ellenhorn and Barceloux: Medical Toxicology]

It has been suggested that there is a need for establishing a new biological exposure limit before a workshift that is clearly below 100 mmol ethoxy-acetic acids per mole creatinine in morning urine of people occupationally exposed to ethylene glycol ethers. This arises from the finding that an increase in urinary stones may be associated with such exposures.

Laitinen J., et al: Occupational & Environmental Medicine 1996; 53, 595-600

To treat poisoning by the higher aliphatic alcohols (up to C7):

- Gastric lavage with copious amounts of water.
- It may be beneficial to instill 60 ml of mineral oil into the stomach.
- Oxygen and artificial respiration as needed.

- Electrolyte balance: it may be useful to start 500 ml. M/6 sodium bicarbonate intravenously but maintain a cautious and conservative attitude toward electrolyte replacement unless shock or severe acidosis threatens.
- To protect the liver, maintain carbohydrate intake by intravenous infusions of glucose.
- + Haemodialysis if coma is deep and persistent. [GOSSELIN, SMITH HODGE: Clinical Toxicology of Commercial Products, Ed 5)

BASIC TREATMENT

• Watch for signs of respiratory insufficiency and assist ventilation as necessary.

[•] Establish a patent airway with suction where necessary.

Issue Date: 01/01/2013 Print Date: 06/11/2014

New Holland NH Premix 50

- Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- Monitor and treat, where necessary, for shock.
- Monitor and treat, where necessary, for pulmonary oedema.
- Anticipate and treat, where necessary, for seizures.
- DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.
- Give activated charcoal.

ADVANCED TREATMENT

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- If the patient is hypoglycaemic (decreased or loss of consciousness, tachycardia, pallor, dilated pupils, diaphoresis and/or dextrose strip or glucometer readings below 50 mg), give 50% dextrose.
- + Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

EMERGENCY DEPARTMENT

- Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime. Other useful analyses include anion and osmolar gaps, arterial blood gases (ABGs), chest radiographs and electrocardiograph.
- Positive end-expiratory pressure (PEEP)-assisted ventilation may be required for acute parenchymal injury or adult respiratory distress syndrome.
- Acidosis may respond to hyperventilation and bicarbonate therapy.
- · Haemodialysis might be considered in patients with severe intoxication.
- Consult a toxicologist as necessary. BRONSTEIN, A.C. and CURRANCE, P.L. EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

For C8 alcohols and above.

Symptomatic and supportive therapy is advised in managing patients.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

U	
	The product contains a substantial proportion of water, therefore there are no restrictions on the type of extinguishing media which may be used. Choice of extinguishing media should take into account surrounding areas.
	Though the material is non-combustible, evaporation of water from the mixture, caused by the heat of nearby fire, may
	produce floating layers of combustible substances.
	In such an event consider:
	▶ foam.

Special hazards arising from the substrate or mixture

Fire Incompatibility

Advice for firefighters Fire Fighting Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. Non combustible. Not considered to be a significant fire risk. Expansion or decomposition on heating may lead to violent rupture of containers. Decomposes on heating and may produce toxic fumes of carbon monoxide (CO).

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

0		
	Major Spills	Slippery when spilt. Moderate hazard. Clear area of personnel and move upwind.

SIGHT NO. 3.1.1.1	New Holland NH Premix 50	`	
	 Alert Fire Brigade and tell them location and nature of hazard. 		
	Personal Protective Equipment advice is contained in Section 8 of the MSDS.		

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

	5
Safe handling	 DO NOT allow clothing wet with material to stay in contact with skin Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Avoid contact with moisture.
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers.

Conditions for safe storage, including any incompatibilities

Suitable container	 DO NOT use aluminium or galvanised containers Polyethylene or polypropylene container. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	 Avoid oxidising agents, acids, acid chlorides, acid anhydrides, chloroformates. *

PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia ExposureethyleneStandardsglycol		Ethylene glycol (particulate) / Ethylene glycol (vapour)	10 mg/m3 / 52 mg/m3 / 20 ppm	104 mg/m3 / 40 ppm	Not Available	Sk
Australia Exposure Standards	sodium molybdate	Molybdenum, soluble compounds (as Mo)	5 mg/m3	Not Available	Not Available	Not Available

molybdate	(as Mo)					Available	Available	
EMERGENCY LIMITS								
TEEL-0		TEEL-1		TEEL-2		TEEL-3		
Not Available		Not Available		Not Available	Not Available		Not Available	
		·						
Original IDLH					Revised IDLH			
Not Available					Not Available			
Not Available				Not Available				
Not Available				Not Available				
Not Available				Not Available				
Not Available				Not Available				
Not Available					Not Available			
Not Available	Not Available				Not Available			
N.E. mg/m3 / N.	N.E. mg/m3 / N.E. ppm				1,000 mg/m3			
Not Available	Not Available				Not Available			
Not Available				Not Available				
Not Available				Not Available				
	TEEL-0 Not Available Original IDLH Not Available Not Available	TEEL-0 Not Available Original IDLH Not Available Not Available	TEEL-0 TEEL-1 Not Available Not Available Original IDLH Not Available Not Available Image: Comparison of the state of the st	TEEL-0 TEEL-1 Not Available Not Available Original IDLH Not Available Not Available Image: Comparison of the state of the st	TEEL-0 TEEL-1 TEEL-2 Not Available Not Available Not Available Original IDLH Image: Comparison of the strength of the strengen of the strengt of	TEEL-0 TEEL-1 TEEL-2 Not Available Not Available Not Available Original IDLH Revised IDLH Not Available Not Available Not Available Not Available <	TEEL-0 TEEL-1 TEEL-2 TEEL-3 Not Available Not Available Not Available Not Available Original IDLH Revised IDLH Not Available Not Available Not Available Not Available	

Page 6 of 11

New Holland NH Premix 50

Exposure controls	
Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.
Personal protection	
Eye and face protection	 Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
Skin protection	See Hand protection below
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber
Body protection	See Other protection below
Other protection	 Overalls. P.V.C. apron. Barrier cream.
Thermal hazards	Not Available

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

New Holland NH Premix 50

Material	CPI
BUTYL	С
NATURAL RUBBER	С
NATURAL+NEOPRENE	С
NEOPRENE	С
NEOPRENE/NATURAL	С
NITRILE	C
NITRILE+PVC	С
PE/EVAL/PE	С
PVA	С
PVC	С
TEFLON	С
VITON	С

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion
C: Poor to Dangerous Choice for other than short term immersion
NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. * Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Blue liquid with a mild odour; mixes with water.
------------	--

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 5 x ES	A-AUS / Class 1 P2	-	A-PAPR-AUS / Class 1 P2
up to 25 x ES	Air-line*	A-2 P2	A-PAPR-2 P2
up to 50 x ES	-	A-3 P2	-
50+ x ES	-	Air-line**	-

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Physical state	Liquid	Relative density (Water = 1)	1.07
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Non Combustible	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Non Combustible	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution(1%)	Not Available
Vapour density (Air = 1)	>2	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Exposure to aliphatic alcohols with more than 3 carbons may produce central nervous system effects such as headache, dizziness, drowsiness, muscle weakness, delirium, CNS depression, coma, seizure, and neurobehavioural changes. Symptoms are more acute with higher alcohols. Respiratory tract involvement may produce irritation of the mucosa, respiratory insufficiency, respiratory depression secondary to CNS depression, pulmonary oedema, chemical pneumonitis and bronchitis. Cardiovascular involvement may result in arrhythmias and hypotension.
Ingestion	Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. Effects on the nervous system characterise over-exposure to higher aliphatic alcohols. These include headache, muscle weakness, giddiness, ataxia, (loss of muscle coordination), confusion, delirium and coma. Gastrointestinal effects may include nausea, vomiting and diarrhoea.
Skin Contact	 The material may produce mild skin irritation; limited evidence or practical experience suggests, that the material either: produces mild inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant, but mild, inflammation when applied to the healthy intact skin of animals (for up to four hours), such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (non allergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.

Eye	Limited evidence or practical experience suggests, that the material may cause moderate eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged exposure may cause moderate inflammation (similar to windburn) characterised by a temporary redness of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur. The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.		
Chronic	There is some evidence to provide a presumption that human exposure to the material may result in impaired fertility on the basis of: some evidence in animal studies of impaired fertility in the absence of toxic effects, or evidence of impaired fertility occurring at around the same dose levels as other toxic effects but which is not a secondary non-specific consequence of other toxic effects.		
New Holland NH Premix 50	TOXICITY Not Available	IRRITATION Not Available	
ethylene glycol	TOXICITY Dermal (rabbit) LD50: 9530 mg/kg Inhalation (rat) LC50: 50100 mg/m3/8 hr	IRRITATION Eye (rabbit): 100 mg/1h - mild Eye (rabbit): 12 mg/m3/3D	
	Oral (rat) LD50: 4700 mg/kg Not Available	Eye (rabbit): 1440mg/6h-moderate Eye (rabbit): 500 mg/24h - mild Skin (rabbit): 555 mg(open)-mild Not Available	
potassium phosphate, monobasic	TOXICITY Not Available	IRRITATION Not Available	
sodium nitrite	TOXICITY Inhalation (rat) LC50: 5.5 mg/m3/4H Oral (rat) LD50: 180 mg/kg Not Available	IRRITATION Eye (rabbit): 500 mg/24hr - mild Not Available	
sodium nitrate	TOXICITY Oral (rabbit) LD50: 2680 Mg/kg Oral (rat) LD50: 1267 mg/kg Not Available	IRRITATION Nil reported Not Available	
sodium molybdate	TOXICITYInhalation (Rat) LC50: >2080 mg/m3/4hIntraperitoneal (Mouse) LD50: 257 mg/kgIntraperitoneal (Mouse) LD50: 303 mg/kgIntraperitoneal (Rat) LD50: 520 mg/kgIntraperitoneal (Rat) LD50: 576 mg/kgIntravenous (Cat) LD50: 917 mg/kgOral (Dog) LD50: 250 mg/kgOral (Guinea pig) LD50: 310 mg/kgOral (Rat) LD50: 250 mg/kgOral (Rat) LD50: 250 mg/kgOral (Rat) LD50: 250 mg/kgOral (Rat) LD50: 4000 mg/kg		

	Subcutaneous (Mouse) LD50: 570 mg/kg	
	Not Available	Not Available
	ΤΟΧΙCΙΤΥ	IRRITATION
sodium metasilicate,	Oral (rat) LD50: 1153 mg/kg	Skin (human): 250 mg/24h SEVERE
pentahydrate		Skin (rabbit): 250 mg/24h SEVERE
	Not Available	Not Available
	ΤΟΧΙCΙΤΥ	IRRITATION
water	Not Available	Not Available

Not available. Refer to individual constituents.

SKIN

ethylene glycol

ETHYLENE GLYCOL	For ethylene glycol: Ethylene glycol is quickly and extensively absorbed through the gastrointestinal tract. Limited information suggests that it is also absorbed through the respiratory tract; dermal absorption is apparently slow. Following absorption, ethylene glycol is distributed throughout the body according to total body water. In most mammalian species, including humans, ethylene glycol is initially metabolised by alcohol. [Estimated Lethal Dose (human) 100 ml; RTECS quoted by Orica] Substance is reproductive effector in rats (birth defects). Mutagenic to rat cells.		
POTASSIUM PHOSPHATE, MONOBASIC	No data of toxicological significance identified in literature search.		
SODIUM NITRITE	The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. Tumorigenic - Carcinogenic by RTECS criteria.		
SODIUM METASILICATE, PENTAHYDRATE	The material may be irritating to the eye, with p irritants may produce conjunctivitis. Asthma-like symptoms may continue for mont to a non-allergenic condition known as reactive exposure to high levels of highly irritating comp sodium metasilicate anhydrous:	hs or even years after expose a airways dysfunction syndro	-
WATER	No significant acute toxicological data identified	d in literature search.	
SODIUM NITRATE, SODIUM MOLYBDATE	Asthma-like symptoms may continue for mont to a non-allergenic condition known as reactive exposure to high levels of highly irritating comp preceding respiratory disease, in a non-atopic minutes to hours of a documented exposure to of moderate to severe bronchial hyperreactivit inflammation, without eosinophilia, have also b	e airways dysfunction syndro pound. Key criteria for the di individual, with abrupt onset the irritant. A reversible airfl y on methacholine challenge	me (RADS) which can occur following agnosis of RADS include the absence of of persistent asthma-like symptoms within ow pattern, on spirometry, with the presence e testing and the lack of minimal lymphocytic
Acute Toxicity	¥	Carcinogenicity	✓
Skin Irritation/Corrosion	0	Reproductivity	0
Serious Eye Damage/Irritation	0	STOT - Single Exposure	0
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	*
Mutagenicity	×	Aspiration Hazard	0
CMR STATUS		🗙 – Data ava	iired to make classification available ilable but does not fill the criteria for classification Available to make classification

Australia Exposure Standards - Skin

Sk

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Harmful to aquatic organisms. **DO NOT** discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ethylene glycol	LOW (Half-life = 24 days)	LOW (Half-life = 3.46 days)
sodium nitrite	HIGH	HIGH
sodium nitrate	HIGH	HIGH
sodium molybdate	LOW	LOW
water	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
ethylene glycol	LOW (BCF = 3.162)
sodium nitrite	LOW (BCF = 3.162)
sodium nitrate	LOW (BCF = 3.162)
sodium molybdate	LOW (BCF = 10.38)
water	LOW (BCF = 3.162)

Mobility in soil

Ingredient	Mobility
ethylene glycol	HIGH (KOC = 1)
sodium nitrite	LOW (KOC = 23.74)
sodium nitrate	LOW (KOC = 14.3)
sodium molybdate	LOW (KOC = 48.64)
water	LOW (KOC = 14.3)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

	 Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no
Product / Packaging	suitable treatment or disposal facility can be identified.
disposal	• Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or incineration in
	a licenced apparatus (after admixture with suitable combustible material).
	Decontaminate empty containers.

SECTION 14 TRANSPORT INFORMATION

Marine Pollutant NO HAZCHEM Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL 73 / 78 and the IBC code

Source	Ingredient	Pollution Category
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	ethylene glycol	Y

IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	sodium nitrite	Υ
---	----------------	---

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

ethylene glycol(107-21-1) is found on the following regulatory lists	"Australia Exposure Standards","Australia Inventory of Chemical Substances (AICS)","Australia Hazardous Substances Information System - Consolidated Lists"
potassium phosphate, monobasic(7778-77-0) is found on the following regulatory lists	"Australia Inventory of Chemical Substances (AICS)"
sodium nitrite(7632-00-0) is found on the following regulatory lists	"International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "Australia Inventory of Chemical Substances (AICS)", "Australia Hazardous Substances Information System - Consolidated Lists"
sodium nitrate(7631-99-4) is found on the following regulatory lists	"Australia Inventory of Chemical Substances (AICS)"
sodium molybdate(7631-95-0) is found on the following regulatory lists	"Australia Exposure Standards","Australia Inventory of Chemical Substances (AICS)","Australia Hazardous Substances Information System - Consolidated Lists"
sodium metasilicate, pentahydrate(10213-79-3) is found on the following regulatory lists	"Australia Inventory of Chemical Substances (AICS)", "Australia Hazardous Substances Information System - Consolidated Lists"
water(7732-18-5) is found on the following regulatory lists	"Australia Inventory of Chemical Substances (AICS)"

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.