



NEW HOLLAND TT4

TT4.55 | TT4.65 | TT4.75 | TT4.90



MODELS	TT4.55	TT4.65	TT4.75	TT4.90
ENGINE				
No. Cylinders / Aspiration / valves / emission level	3 / T / 2 / Tier III	3 / T / 2 / Tier III	3 / T / 2 / Tier III	4 / T / 2 / Tier III
Approved Biodiesel Blend	B100	B100	B100	B100
Capacity (Litres)	2.9	2.9	2.9	3.9
Rated Power ISO TR14396-ECE R120 (kW/hp) @ rated speed	41 / 55 @ 2300	48 / 65 @ 2300	55 / 75 @ 2300	66 / 88 @ 2300
PTO Power at Rated Speed (kW/hp)	36.6 / 49	42.5 / 57	48.5 / 66.0	55.2 / 74.0
Maximum Torque (Nm)	220	270	300	340 @ 1400
Torque Rise (%)	30	30	30	25
Fuel Capacity (Litres) Main + Auxillary (not applicable on TT4.90)	60 + 40	60 + 40	60 + 40	90
TRANSMISSION				
Syncho - Mechanical Forward / Reverse shuttle (Dash mounted)	●	●	●	N/A
Hydraulic Power Shuttle (Dash mounted)	○	○	○	●
12 x 12 Mechanical Synchromesh transmission	●	●	●	●
Minimum speed / Maximum road speed (kph)*	1.56 / 32.05	1.56 / 32.23	1.56 / 34.4	1.72 / 35.8
20 x 20 Mechanical Powershuttle transmission with creeper	○	○	○	○
Creeper - Minimum speed / Maximum road speed (kph)*	0.27 / 32.05	0.27 / 32.05	0.27 / 32.05	0.30 / 35.8
FRONT AXLES				
4WD front axle	●	●	●	●
2WD front axle	○	○	○	○
Steering angle 4WD (°)	55	55	55	55
Minimum Turn Radius Less Brakes 4WD (mm)	6.0	6.0	6.4	5.1
REAR AXLE				
Planetary reduction final drive	●	●	●	●
Differential lock (Mechanically engaged)	●	●	●	●
Oil immersed multidisc braking system	●	●	●	●
HYDRAULICS				
Main pump flow / pump pressure (Lpm / Bar)	54 / 207	54 / 207	54 / 207	54 / 207
Independent steering pump flow / pump pressure (Lpm / Bar)	28.8 / 210	28.8 / 210	28.8 / 210	33 / 207
Rear Auxiliary Remote Valves (Std / Max number)	1 / 3	1 / 3	1 / 3	2 / 3
LINKAGE				
Category	I / II	I / II	I / II	I / II
Lift capacity @ ball ends	2500	2500	2500	2500
Lift capacity @ 610mm behind ball ends	1845	1845	1845	1845
Swinging drawbar	●	●	●	●
PTO				
Independent rear PTO	●	●	●	●
Rear PTO	540 / 540E	540 / 540E	540 / 540E	540 / 540E
Rear PTO Engine Speed at 540 rpm	2217	2217	2217	2217
Rear PTO Engine Speed at 540E rpm	1715	1715	1715	1715
OPERATOR ENVIRONMENT				
Mechanical suspension seat with seat belt on inclined plane	●	●	●	●
Suspension Travel (mm)	90	90	90	90
Flat deck Operator Area	●	●	●	●
Suspended Brake and Clutch pedals	●	●	●	●
Canopy	●	●	●	●
Two post Foldable ROPS platform	●	●	●	●
DIMENSIONS				
Wheelbase 2WD / 4WD (mm)	2079 / 2010	2079 / 2010	2200 / 2145	2283 / 2258
Overall length with front weights 2WD / 4WD (mm)	3875	3875	3875	4059
Overall Width 2WD / 4WD (mm)	1965	1965	2041	2041
Height to top of ROPS 2WD / 4WD (mm)	2538	2566	2589	2589
Height to top of Exhaust 2WD / 4WD (mm)	2435	2464	2487	2487
Height to top of Steering wheel 2WD / 4WD (mm)	1754	1782	1810	1814
Ground clearance under front axle 2WD / 4WD (mm)	504	504	504	504 / 416
Shipping Weight ROPS 2WD / 4WD (kg)	2286 / 2640	2400 / 2795	2514 / 2935	2825 / 3085
Maximum ballasted weight 2WD / 4WD (kg)	2690 / 2755	3080 / 3145	3080 / 3145	3860 / 3990

NEW HOLLAND AP PLUS SERIES LOADER

MODELS	AP 30 PLUS	AP32 PLUS	AP32 PLUS	AP32 PLUS
Mechanical self levelling	●	●	●	●
Easy detach loader frame	●	●	●	●
Auto-Locking Attachment Quick Coupler	●	●	●	●
Includes Tractor / Loader Sub Frame	●	●	●	●
Loader Valve & Joystick Control	○	○	○	○
Bonnet Grille Guards	○	○	○	○
Maximum lift height to pivot pin (mm)	3100	3240	3240	3240
Maximum dump angle (°)	58	58	58	58
Digging depth (mm)	150	150	150	150
Reach at maximum lift height (mm)	1060	1360	1360	1360
Reach with bucket on ground (mm)	1950	2200	2200	2200

● Standard ○ Optional *Speed with Standard tyres

AT YOUR OWN DEALER



YOUR SUCCESS – OUR SPECIALTY

Visit our web site at: www.newholland.com - tel: +61 2 9673 7777
31-53 Kurrajong Road, St Marys NSW 2760



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.

The data indicated in this folder are approximate. The models described here can be subjected to modifications without any notice by the manufacturer. The drawings and photos may refer to equipment that is either optional or intended for other countries. Please apply to our Sales Network for any further information. Published by New Holland Brand Communications. - Printed in Australia - 15NHXX000 12/15