



SUPER SERIES



INTRODUCING

NEW
3230 TX Super
45 HP (33.55 kW)

NOW WITH ENHANCED POWER OF **45hp**

**JAAN AUR SHAAN KA
NAYA NAAM**



Maximum Useful
Power in Category



Eptara
PTO



Independent
PTO Clutch Lever



HP Hydraulic 1800
Kg Lifting Capacity*



Double Metal
Face Sealing



Straight Axle
Planetary Drive



8F+8R Speed
Synchro Shuttle**



4WD also available
in MHD & STS Axle

*Applicable from 2nd October 2020. T&C apply
**Lifting Capacity at 3-Point Linkage. **Optional. 1 hp = 0.7457 kW

Super Series brings the best of Power & Technology for you...



PTO Power

NH 3230 TX SUPER	39
JD 5042D PowerPro	36
MM 475XP+/575DI BP	39/39.4
ESC FT45/PT Euro42+	36.8/38
EICHER 485	38

Maximum useful power (PTO POWER) indicates a powerful tractor & capable for one size bigger implement - Less RPM drop & slippage resulting in fast & more area coverage.



Eptraa PTO

NH 3230 TX SUPER	Yes
JD 5042D PowerPro	No
MM 475XP+/575DI BP	No
ESC FT45/PT Euro42+	No
EICHER 485	No

First time in India, there are Seven PTO speeds in a single tractor. Saves more diesel by selecting appropriate PTO speeds for various equipments - longer durability.



Independent PTO Clutch Lever

NH 3230 TX SUPER	Yes
JD 5042D PowerPro	Yes
MM 475XP+/575DI BP	No
ESC FT45/PT Euro42+	No
EICHER 485	No

Freedom from pressing half clutch & full clutch. SOFTEK CLUTCH gives less maintenance & longer life.



HP Hyd. Lift Capacity (Kg)

NH 3230 TX SUPER	1800
JD 5042D PowerPro	1600
MM 475XP+/575DI BP	1500
ESC FT45/PT Euro42+	1600
EICHER 485	1200-1850*

Uniform depth in seeding & ploughing, resulting in more productivity and double profits. Lift-O-matic and 30L/min hydraulic pump flow helps in all hydraulic functions.



Double Metal Face Sealing

NH 3230 TX SUPER	Yes
JD 5042D PowerPro	No
MM 475XP+/575DI BP	No
ESC FT45/PT Euro42+	No
EICHER 485	No

Ability to work in deep puddling fields with low maintenance. Metal Face Sealing is given both at Rear Axle & PTO - no water entering, keeping the Hydraulic & Rear Axle safe.



Straight Axle Planetary Drive

NH 3230 TX SUPER	Yes
JD 5042D PowerPro	Yes
MM 475XP+/575DI BP	No
ESC FT45/PT Euro42+	No
EICHER 485	No

Distribution of rear axle loads over three points for reduced stress on individual gears and shafts, resulting in longer life with less service & maintenance time.



8+8 Synchro Shuttle

NH 3230 TX SUPER	Yes
JD 5042D PowerPro	No
MM 475XP+/575DI BP	No
ESC FT45/PT Euro42+	No
EICHER 485	No

Facility of easy forward & reverse movement of tractor without taking operator's hand off the steering wheel. Less time consuming - more area coverage and high productivity.



Constant Mesh AFD

NH 3230 TX SUPER	Yes
JD 5042D PowerPro	Yes
MM 475XP+/575DI BP	No
ESC FT45/PT Euro42+	Yes
EICHER 485	No

Finger touch side shift - Easy gear operation, facility of changing gears even at high speeds. Long clutch life and minimum maintenance.

USAGE IN VARIOUS APPLICATIONS



Cultivator - 9 Tynes



Rotavator - 6 Feet



Reversible Plough - 2 Bottom



Puddling - Rotavator with 4WD Tractor



Haulage



Mini Baler

CNH INDUSTRIAL (INDIA) PVT. LTD. {FORMERLY KNOWN AS NEW HOLLAND FIAT (INDIA) PVT. LTD.}
Plot No. 03, Udyog Kendra, Greater Noida, District Gautam Budh Nagar, Uttar Pradesh.

Authorised Dealer

TOLL-FREE NO.
1800-419-0124
www.newholland.com/in

Note: New Holland believes in constantly working to bring improvements in their products. Therefore, the specifications given above may be changed without any prior notice. For latest information, contact your nearest dealership.
The specifications given above are taken from the sub-clause of CFMTTI, Budni, Report/manufacturer's website/product leaflet. The above mentioned information is intended for internal training purposes only.