



# SUPER SERIES



— INTRODUCING —

**NEW**  
**3600-2 TX** *Super*  
**49.5 HP (36.91 kW)**

NOW WITH **STRAIGHT AXLE PLANETARY DRIVE**

\*Lifting Capacity at 3-Point Linkage. \*Optional. 1 hp = 0.7457 kW

## JAAN AUR SHAAN KA NAYA NAAM



**FPT Engine**  
Powerful & Fuel Efficient



**Eptara  
PTO**



**Independent  
PTO Clutch Lever**



**HP Hydraulic 1800  
Kg Lifting Capacity\***



**Double Metal  
Face Sealing**



**Highest Wheelbase  
Potato/Onion Track Width**



**8F+8R Speed  
Synchro Shuttle\***



**4WD\* also available  
in MHD & STS Axle**

## Super Series brings the best of Power & Technology for you...



### PTO Power

NH 3600-2 TX SUPER	46
JD 5050D	42.6
MM 585DI POWER+	45
ESC FT50PM/PT Euro50	42/45.5
ITL Sik. DLX DI/Rx50 S1	45.8

Maximum useful power (PTO POWER) indicates a powerful tractor & capable for one size bigger implement - Less RPM drop & slippage resulting in fast & more area coverage.



### Eptara PTO

NH 3600-2 TX SUPER	Yes
JD 5050D	No
MM 585DI POWER+	No
ESC FT50PM/PT Euro50	No
ITL Sik. DLX DI/Rx50 S1	No

First time in India, there is Seven PTO speeds in a single tractor. Saves more diesel by selecting appropriate PTO speeds for various equipments - long durability.



### Independent PTO Clutch Lever

NH 3600-2 TX SUPER	Yes
JD 5050D	Yes
MM 585DI POWER+	No
ESC FT50PM/PT Euro50	No
ITL Sik. DLX DI/Rx50 S1	No

Freedom from pressing half clutch & full clutch. SOFTEK CLUTCH gives less maintenance & longer life.



### Straight Axle Planetary Drive

NH 3600-2 TX SUPER	Yes
JD 5050D	Yes
MM 585DI POWER+	No
ESC FT50PM/PT Euro50	Yes/No
ITL Sik. DLX DI/Rx50 S1	No

Distribution of rear axle loads over three points for reduced stress on individual gears and shafts, resulting in longer life with less service & maintenance time.



### Double Metal Face Sealing

NH 3600-2 TX SUPER	Yes
JD 5050D	No
MM 585DI POWER+	No
ESC FT50PM/PT Euro50	No
ITL Sik. DLX DI/Rx50 S1	No

Ability to work in deep puddling fields with low maintenance. Metal Face Sealing is given both at Rear Axle & PTO - no water entering, keeping the Hydraulic & Rear Axle safe.



### 8+8 Synchro Shuttle

NH 3600-2 TX SUPER	Yes
JD 5050D	No
MM 585DI POWER+	No
ESC FT50PM/PT Euro50	No
ITL Sik. DLX DI/Rx50 S1	No

Facility of easy forward & reverse movement of tractor without taking operator's hand off the steering wheel. Less time consuming - more area coverage and high productivity.



### HP Hyd. Lift Capacity (kg)

NH 3600-2 TX SUPER	1800 kg
JD 5050D	1600 kg
MM 585DI POWER+	1640 kg
ESC FT50PM/PT Euro50	1800/2000 kg
ITL Sik. DLX DI/Rx50 S1	1800 kg

Uniform depth in seeding & ploughing, resulting in more productivity and double profits. Lift-O-matic and 38L/min hydraulic pump flow helps in all hydraulic functions.



### Highest Wheelbase - 2104 mm & Potato/Onion Track Width 48 inch

NH 3600-2 TX SUPER	Yes
JD 5050D	No
MM 585DI POWER+	No
ESC FT50PM/PT Euro50	No
ITL Sik. DLX DI/Rx50 S1	No

More stable & comfortable ride, reducing the possibility of front lifting in load and best suitable for Potato/Onion applications.

## USAGE IN VARIOUS APPLICATIONS



Rotavator - 7 Feet



Reversible Plough - 2 Bottom



Puddling - Rotavator with 4WD Tractor



Heavy Haulage



Straw Reaper



Cultivator

**CNH INDUSTRIAL (INDIA) PVT. LTD.** {FORMERLY KNOWN AS NEW HOLLAND FIAT (INDIA) PVT. LTD.}  
Plot No. 03, Udyog Kendra, Greater Noida, District Gautam Budh Nagar, Uttar Pradesh.

Authorised Dealer

**TOLL-FREE NO.**  
**1800-419-0124**  
[www.newholland.com/in](http://www.newholland.com/in)

Note: New Holland believes in constantly working to bring improvements in their products. Therefore, the specifications given above may be changed without any prior notice. For latest information, contact your nearest dealership. The specifications given above are taken from the sub-clause of CFMTTI, Budni, Report/manufacturer's website/product leaflet. The above mentioned information is intended for internal training purposes only.