

# T6000 DELTA ROPS

T6020 Delta ROPS | T6050 Delta ROPS





Model	T6020 Delta ROPS	T6050 Delta ROPS
<b>Engine</b>	<b>FPT Industrial</b>	<b>FPT Industrial</b>
No. of cylinders / Capacity / Emissions level	4 / 4485 / Tier III	6 / 6728 / Tier III
Rated power - ISO 14396/EC R120 (kW/hp[cv])	82 / 112	93 / 127
Max. power - ISO 14396/EC R120 (kW/hp[cv])	82 / 112	93 / 127
Rated speed	2200 rpm	
Max. torque ISO 14396 (standard/Engine Power Management (Nm))	510 @ 1250	555 @ 1250
Torque rise % (maximum)	43	38
Aspiration	Turbocharged	
Intercooling	Air-to-air intercooled	
<b>Electrical</b>		
Standard alternator	120-amp, 12-volt	
Battery capacity (heavy-duty)	960 CCA	
<b>Transmission and PTO</b>		
16 x 16 ElectroShift™	Standard	
PTO – 'Soft Start'	Standard	
2-speed 540/1000 with additional 21-spline 1 3/8" shaft	Standard	
<b>Front axle</b>		
Conventional 4WD axle with limited slip	Standard	
<b>Hydraulic system</b>		
Load-sensing hydraulic type	Open centre	
Rear remotes	3 standard, 4 optional	
Mid mount remotes	2 x mechanical mid mount, loader ready brackets	
Main/implement pump flow	63 l/min	
Steering and services pump flow	47 l/min	
Total tractor hydraulic flow	110 l/min	
<b>Rear 3-point hitch</b>		
Draft control	Mechanical	
3-point hitch category	Cat II/IIIN quick attach	
3-point hitch lift capacity—standard/optional	4170 kg @ ball ends	
<b>Capacities</b>		
Fuel tank	176 litres	250 litres
Engine oil	10 litres	15 litres
Hydraulic fluid	62 litres	62 litres
<b>Operator environment</b>		
Operator platform	Folding ROPS frame with plastic canopy (sunshade)	
Operator access	Left- and right-hand steps	
Seat	Deluxe mechanical suspension and belt	
Fender mounted external linkage controls	External lift control for MDC	
Rear view mirrors	Manual adjust	
<b>Tyres and wheel equipment</b>		
Rear tyres	600/65R34	600/65R38
Front tyres	480/65R24	480/65R28
Front fenders	480mm static	
<b>Dimensions</b>		
Standard 4WD ROPS	4280 kg	4700 kg
Height to top of ROPS	2856 mm	2898 mm
Height to top of exhaust	2775 mm	2819 mm
4WD track width adjustability	1580 - 2337 mm	
Wheelbase (4WD)	2412 mm	2652 mm



[www.newholland.co.nz](http://www.newholland.co.nz)

The data indicated in this folder are approximate. The models described here can be subjected to modifications without any notice by the manufacturer. The drawings and photos may refer to equipment that is either optional or intended for other countries. Please apply to our Sales Network for any further information. Published by New Holland Brand Communications. Bts Adv. - Printed in New Zealand - 10/19 - 19NH049