

BOOMER 25 Compact



NEW BOOMER 25 COMPACT. SMALL BUT MIGHTY.

The new Boomer™ 25 Compact tractor is the best choice for AG-lifestylers, groundcare professionals and municipalities who need a hard-working, versatile small tractor to handle the chores a garden tractor just can't. It's ready to take on your yard, landscape, gardening and property maintenance jobs. Its compact size makes it easy to operate and maneuver around obstacles and in confined spaces. Known for delivering outstanding value, these reliable, powerful and easy-to-operate compacts will help you complete tasks efficiently while being easy on your wallet.



TRACTION ENHANCING FOUR-WHEEL DRIVE (4WD)

When it's slippery and wet there is no need to fret. The Boomer 25 Compact's standard, mechanically engaged 4WD will power you through the tough spots. With standard power steering and its 4WD axle's tight turning design, maneuvering the Boomer 25 Compact in tight spaces, even with a full bucket, is easy.





MORE HYDRAULIC FLOW = EFFICIENT ATTACHMENT OPERATION

Boomer's robust hydraulic system provides 17.4Lpm of dedicated flow for implement/attachment operation. With over 450kg of 3-PT lift capacity you will be able to make the most of heavy implements like a rotary cutter, box blade or tiller. A separate 8Lpm steering pump ensures low effort maneuvering at all times.



INFINITE SPEEDS, INFINITE EASE

The 2-range hydrostatic transmission delivers an infinite speed choice to better match your needs. The forward and reverse pedals feature anti-slip rubber pads that are color coded and embossed with their direction of travel for sure, safe operation every time. Lots to mow? Then you will appreciate the standard cruise control which will make hectares and hours fly by.



POWER TO LOAD, MOW AND MORE

The Boomer 25 Compact tractor features a Stage V compliant, naturally aspirated, rugged, reliable and fuel efficient 3 cylinder diesel engine, delivering 25hp(CV) at 3000rpm: more than enough to perform your toughest chores. The large fill opening, 25L fuel tank lets you complete more tasks between easy fill-ups. Boomer saves you time and money when it comes to maintenance, too. Convenient access to service points makes performing routine maintenance quick and easy.



COMFORTABLE OPERATION STARTS WITH THE RIGHT SEAT

Step onto the spacious operator's platform where a deluxe, high back cushion, adjustable backrest seat awaits you. Once in the Boomer's seat you will be surprised at just how much room there is. You will be always informed thanks to a modern, automotive-style instrument cluster, while deluxe pods, which contain transmission range, 4WD, PTO and 3-PT selection levers, flank you and fall intuitively to hand.



INTEGRATED MOWER DECK

The optional 160GMS mid-mounted mower deck features quick and easy installation and removal, a 1520mm cutting width and side discharge, providing outstanding cutting performance.



FRONT LOADER

The optional 105LC loader is designed to perfectly fit the Boomer 25 Compact and its high strength design features mechanical self leveling and quick and easy mounting and dismounting. With a useful 455kg lift capacity and 1830mm max lift height, matched to a skid steer style attachment coupler, no job is too small for this compact combination.

Model		BOOMER 25 COMPACT
Engine		
No. of cylinders / Capacity / Emissions Level	(cm ³)	3 / 1260 / Stage V
Aspiration		Natural
Gross engine power @3000rpm	[kW/hp(CV)]	18.4/24.7
Fuel tank capacity	(L)	25
Alternator	(amps)	50
PTO		
Rear PTO		●
Mid PTO		●
PTO horsepower	[hp(CV)]	12.8
PTO speed (rear)	(rpm)	540
PTO speed (mid)	(rpm)	2000
PTO type		Independent electro-hydraulic engagement
Transmission		
Type / control		2 range hydrostatic / dual pedal
Maximum forward speed	(kph)	14.7
HST Cruise control		●
Rear diff-lock engagement		Mechanical
Brake type		Wet, multi-disc
Hydraulics		
Implement hydraulic flow	(Lpm)	17.4
Steering hydraulic flow	(Lpm)	8
Total flow	(Lpm)	25.4
Remote valves (mid-mounted, joystick control)		2
3-Point hitch		Chain type stabilizers / fixed link ends
Rear lift capacity at ball ends	(kg)	450
Rear lift capacity 610mm behind ball ends	(kg)	330
Linkage category		1
Front axle		
Four-Wheel Drive		●
Dimensions and weight		
Wheelbase	(mm)	1425
Length	(mm)	2473
Width	(mm)	1187
Height (top of ROPS)	(mm)	2220
Weight	(kg)	655
Mower		
Mounting point		160GMS
Cutting width	(mm)	1520
Front loader		
Max lift capacity	(kg)	105LC
Max lift height	(mm)	455
Max hinge pin height	(mm)	1830
Mechanical self leveling		1650
Skid steer style quick coupler		●
Joystick control		●
		Mechanical

● Standard



www.newholland.com/uk - www.newholland.com/ie

The data indicated in this folder are approximate. The models described here can be subjected to modifications without any notice by the manufacturer. The drawings and photos may refer to equipment that is either optional or intended for other countries. Please apply to our Sales Network for any further information. Published by New Holland Brand Communications. Bts Adv. - Printed in Italy - 11/20 - (Turin) - 190004/INB