

Modelos		E12D	E14D	E17D	E18D	E19D	E20D	E22D	E25D	E28D	E35D	E50D	E55D	E60D	E65D	E15X	E25X
Potencia nominal máxima	[kW/CV]	8,8/11,8		12/16,3		13,7/18,6	13,7/18,6	15,4/20,9	13,7/18,6	18,2/24,7	18,2/24,7	44/59,8		44,3/60,2		11/15	PRÓXIMA- MENTE
Peso en orden de trabajo con techo/cabina ISO 6016	[kg]	1330*/-	1385*/-	1690/1800	1830/1940	1880/1990	2010/2120	2220/2320	2580/2710	3020/3150	-/3400	-/4950	-/5400	-/5970	-/6520	1420*/-	
Anchura máxima	[mm]	790 - 1050		990 - 1250	990 - 1300				1500	1550	1580	1900		1980		790 - 1050	
Altura total	[mm]	2300		2370				2395	2527	2530		2570		2550		2300	
Radio de rotación trasero	[mm]	525	565	650			715	950	750	770	790	950	1050	1000	1100	710	
Profundidad máxima de excavación con brazo de serie/opcional	[mm]	1860/1980	2045/2175	2020/2220	2280/2480	2280/2480	2560/2760	2560/2760	2700/2900	2650/2850	2870/3070	3330/3580	3490/3740	3850/4100	3950/4200	2045/2175	
Altura máx. de descarga brazo de serie/opcional	[mm]	2130/2215	2290/2380	2340/2460	2580/2700	2580/2700	3370/3550	2650/2760	3330/3460	3100/3220	3110/3230	3920/4080	5030/5270	4090/4240	5280/5510	2290/2380	

- No disponible * Con barra antivuelco y techo FOPS 1 ISO 6016