

| Modellen                                           |         | E12D       | E14D      | E17D       | E18D       | E19D      | E20D      | E22D      | E25D      | E28D      | E35D      | E50D      | E55D      | E60D      | E65D      | E15X       | E25X                      |
|----------------------------------------------------|---------|------------|-----------|------------|------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|------------|---------------------------|
| Max. nominaal vermogen                             | [kW/pk] | 8,8/11,8   |           | 12/16,3    |            | 13,7/18,6 | 13,7/18,6 | 15,4/20,9 | 13,7/18,6 | 18,2/24,7 | 18,2/24,7 | 44/59,8   |           | 44,3/60,2 |           | 11,0/15,0  | BINNENKORT<br>BESCHIKBAAR |
| Bedrijfgewicht met overkapping/<br>cabine ISO 6016 | [kg]    | 1330*/–    | 1385*/–   | 1690/1800  | 1830/1940  | 1880/1990 | 2010/2120 | 2220/2320 | 2580/2710 | 3020/3150 | –/3400    | –/4950    | –/5400    | –/5970    | –/6520    | 1420*/–    |                           |
| Maximumbreedte                                     | [mm]    | 790 - 1050 |           | 990 - 1250 | 990 - 1300 |           |           |           | 1500      | 1550      | 1580      | 1900      |           | 1980      |           | 790 - 1050 |                           |
| Totale hoogte                                      | [mm]    | 2300       |           | 2370       |            |           |           | 2395      | 2527      | 2530      |           | 2570      |           | 2550      |           | 2300       |                           |
| Draaistraal achter                                 | [mm]    | 525        | 565       | 650        |            |           | 715       | 950       | 750       | 770       | 790       | 950       | 1050      | 1000      | 1100      | 710        |                           |
| Max. graafdiepte Std/Opt arm                       | [mm]    | 1860/1980  | 2045/2175 | 2020/2220  | 2280/2480  | 2280/2480 | 2560/2760 | 2560/2760 | 2700/2900 | 2650/2850 | 2870/3070 | 3330/3580 | 3490/3740 | 3850/4100 | 3950/4200 | 2045/2175  |                           |
| Max. storthoogte Std/Opt arm                       | [mm]    | 2130/2215  | 2290/2380 | 2340/2460  | 2580/2700  | 2580/2700 | 3370/3550 | 2650/2760 | 3330/3460 | 3100/3220 | 3110/3230 | 3920/4080 | 5030/5270 | 4090/4240 | 5280/5510 | 2290/2380  |                           |

– Niet leverbaar \* met rolbeugel en FOPS 1-dak ISO 6016