

Modeller		E12D	E14D	E17D	E18D	E19D	E20D	E22D	E25D	E28D	E35D	E50D	E55D	E60D	E65D	E15X	E25X
Max. nominell effekt	(kW/hk)	8,8/11,8		12/16,3		13,7/18,6	13,7/18,6	15,4/20,9	13,7/18,6	18,2/24,7	18,2/24,7	44/59,8		44,3/60,2		11,0/15,0	KOMMER SNART
Arbetsvikt med skyddstak/hytt 6016	(kg)	1330*/-	1385*/-	1690/1800	1830/1940	1880/1990	2010/2120	2220/2320	2580/2710	3020/3150	-/3400	-/4950	-/5400	-/5970	-/6520	1420*/-	
Maximal bredd	(mm)	790-1050		990-1250	990-1300				1500	1550	1580	1900		1980		790-1050	
Total höjd	(mm)	2300		2370				2395	2527	2530		2570		2550		2300	
Bakre rotationsradie	(mm)	525	565	650			715	950	750	770	790	950	1050	1000	1100	710	
Max. grävdjup standard-/tillvalsarm	(mm)	1860/1980	2045/2175	2020/2220	2280/2480	2280/2480	2560/2760	2560/2760	2700/2900	2650/2850	2870/3070	3330/3580	3490/3740	3850/4100	3950/4200	2045/2175	
Max. tömningshöjd standard-/tillvalsarm	(mm)	2130/2215	2290/2380	2340/2460	2580/2700	2580/2700	3370/3550	2650/2760	3330/3460	3100/3220	3110/3230	3920/4080	5030/5270	4090/4240	5280/5510	2290/2380	

- Inte tillgänglig \* Roll-Bar och FOPS 1 tak ISO 6016