

WHEEL LOADER

CNH
INDUSTRIAL | CAPITAL



SUPERIORITY IN OPERATIONS

55° dumping angle at
a height of 3.05 m.



PIVOT PINS WITH SEALED GREASE FITTINGS

Low maintenance costs.



PANTOGRAPHIC SYSTEM

Integrated into the loader's
arms, greater visibility while
working.



IMPACT ABSORPTION CONTROL

Hydraulic safety valve, greater
protection against obstacles.



QUICK COUPLING SYSTEM

Shorter attachment
coupling time.



QUICK AND EASY

Coupling and uncoupling is
done in less than a minute.

WHEEL LOADER		430TL	440TL	450TL	460TL
LIFTING HEIGHT					
MAXIMUM HEIGHT AT PIVOT POINT	m	3,75		3,85	
MAXIMUM HEIGHT WITH BUCKET HORIZONTAL	m	3,5		3,6	
MAXIMUM HEIGHT AT DUMPING POSITION	m	2,95		3,05	
WORKING ANGLES					
DUMPING ANGLE	°	52		55	
CARRY ANGLE	°	47		47	
LOAD CAPACITY	kg	1.500		1.900	
BUCKET					
BUCKET WIDTH	m	1,6 / 1,8 / 2,0		1,6/ 1,8 / 2,0 / 2,2	
WEIGHTS	kg	200 to 230		200 to 245	
CUTTING EDGE					
CUTTING EDGE WIDTH	m		2,2		
CUTTING EDGE HEIGHT	m		0,79		
CUTTING EDGE WEIGHT	kg		220		
BIG BAG					
HEIGHT	m		1,82 m		
WEIGHTS	kg		137 kg		
BIG BAG LOAD CAPACITY AT 70° ANGLE	kg	500 kg		1.000 kg	
SPECIFICATIONS					
SELF-LEVELING SYSTEM		DOES NOT HAVE	HAS	DOS NOT HAVE	HAS
WEIGHT WITHOUT ATTACHMENTS	Kg	445	500	475	520
BUCKET LOAD CAPACITY	Kg	780	1.260	1.400	1.540