SÉRIE 30 TRACTORS

THE GREATEST HYDRAULIC LIFTING CAPACITY WITHIN THE CATEGORY

H

PRODUCTIVITY

16x4 Transmission with Dual Power™: solidity, safety and increased torque in extreme conditions.



Uniformity during operations, with lower fuel consumption.

MAINTENANCE COST

Class II HD front axle in a unique piece, selflocking and with armored. crossbars. GREATER EFFICIENCY AND LESS CONSUMPTION NEF4 engine with i-EGR, gas recirculation system: 48% torque reserve.

A Brand of CNH Industrial



www.newholland.com

TECHNICAL SPECIFICATIONS SÉRIE 30

MODELO	7630	8030	
FPT - NEF E	ENGINE		
NOMINAL POWER - ISO TR 14396 @ 2,200 rpm cv (hp)	110 (108)	122 (120)	
MAXIMUM TORQUE AT 1,400 rpm	528 Nm	550 Nm	
NUMBER OF CYLINDERS / DISPLACEMENT	4/4,48	5 cm ³	
TORQUE RESERVE	48%	41%	
SUCTION	TURBO WITH IN	TURBO WITH INTERCOOLER	
INJECTION PUMP	DELP	DELPHI	
FUEL TANK CAB./PLAT.	170	L	
CLUT			
DISC MATERIAL		CERAMETALLIC / ORGANIC	
DIAMETER	14" (356	i mm)	
TRANSMI			
NUMBER OF GEARS - FRONT X REAR		8x2	
OPTIONAL DUALPOWER™ - FRONT X REAR		16x4	
OPTIONAL SUPER-REDUCER AND DUALPOWER™ - FRONT X REAR	24x6	-	
FRONT			
FRONT LOCK		SELF-LOCKING	
DRIVE TRACTION	ELECTRO-H'	ELECTRO-HYDRAULIC	
FRONT AXLE CATEGORY		CLASS II HD	
REAR LOCK	MECHANICAL WITH AUTO	DMATIC DEACTIVATION	
HYDRAULIC			
PUMP FLOW		49 and 80 L / min	
LIFTING CAPACITY AT 610 MM FROM THE SWIVEL (0 AND 1 CYLINDER)		1,840 kgf and 2,910 kgf	
LIFTING CAPACITY AT THE SWIVEL (0 AND 1 CYLINDER)	3,030 kgf and	14,800 kgt	
STEER			
		HYDROSTATIC INDEPENDENT	
HYDRAULIC GEAR PUMP	35 L/r	nin	
		E Ab	
ALTERNATOR BATTERY		12 V / 65 Ah 12 V / 100 Ah	
POWER TA		JUAN	
ACTUATION			
DRIVE AXLE		HYDRAULIC 13/8" 6-SPLINE	
540 RPM TO 1,900 RPM (ENGINE)		STANDARD	
BRAK		ARD	
TYPE		ATH CONTRACTOR OF	
DISCS		OIL BATH 4 DISCS	
PARKING BREAK		4 DISCS MANUAL	
WEIGI			
MAXIMUM WEIGHT ALLOWED	5,900 kg	6,500 kg	
DIMENS		0,000 Kg	
TOTAL LENGTH		mm	
TOTAL HEIGHT		4,330 mm 2,545 mm	
FRONT / REAR TRUNK		1,640 mm / 1,760 mm	



A Brand of CNH Industrial



www.newholland.com