

# AIR DRILL SPECIFICATIONS

## 5500



	<b>5500</b>	
<b>BASE SIZE: ft. (m)</b>	<b>60 (18.3)</b>	<b>70 (21.3)</b>
No. of Sections	5	5
No. of Ranks	4	4
<b>SHANK SPACING: in. (cm)</b>	7.5 (19), 10 (25.4) & 12 (30.5)	
<b>NUMBER OF SHANKS:</b>		
7.5" (19.0 cm) Spacing	96	N/A
10" (25.4 cm) Spacing	72	84
12" (30.5 cm) Spacing	60	70
<b>FRAME WIDTHS:</b>		
Main Frame, ft. in. (m)	10' (3.0)	10' (3.0 m)
Inner Wing, ft. in. (m)	15' (4.6)	15' (4.6 m)
Outer Wing, ft. in. (m)	10' (3.0)	15' (4.6 m)
Transport Width, ft. in. (m)	17'8" (5.4)	17'8" (5.4 m)
Transport Height (max), ft. in. (m)	13'6" (4.1)	13'6" (4.1 m)
<b>WEIGHTS: [All with 350 lb. (159 kg) trips and 3" (7.6 cm) rubber packers]</b>		
7.5" (19.0 cm) Spacing, lb. (kg)	36,300 (16,465)	N/A
10" (25.4 cm) Spacing, lb. (kg)	32,800 (14,878)	36,500 (16,556)
12" (30.5 cm) Spacing, lb. (kg)	31,100 (14,107)	34,400 (15,604)
<b>TIRES:</b>		
Main Frame Casters	11Lx15FI (Duals)	11Lx15FI (Duals)
Inner Wing Casters	11Lx15FI (Duals)	11Lx15FI (Duals)
Outer Wing Casters	11Lx15FI (Singles)	11Lx15FI (Singles)
Rear Transport Wheels	11Lx15FI (Single)*	11Lx15FI (Single)*
*A single tire is used unless machine is configured with 6.5" pneumatic, then those wheels are used for transport.		
<b>Packer Options:</b>	Steel — 3.5" (8.9 cm) / Rubber — 3" (7.6 cm), in-line gang-style	
7.5" (19.0 cm)	Steel — 3.5" (8.9 cm), 4.5" (11.4 cm) / Rubber — 3" (7.6 cm), 4" (10.2 cm),	
10" (25.4 cm) & 12" (30.5 cm)	5.5" (14.0 cm), in-line gang-style + 6.5" (16.5 cm) pneumatic walking beam, gang-style	
	Optional for steel and rubber wheels	
<b>Packer Wheel Mud Scrapers</b>	Standard	
<b>Stone Kickers</b>	Wide range of Flexi-Coil ground openers available	
<b>Openers</b>	Single-shoot and double-shoot	
<b>Air Kits</b>	Basic or expanded blockage monitors available; pin sensors and optical sensors	
<b>Blockage Monitors</b>	Standard; also 31X13.5-15 high flotation available	
<b>Tandem Wheels for Center</b>	Optional; also 31X13.5-15 high flotation available	
<b>Tandem Wheels for Wings</b>	Optional single-bar heavy harrow	
<b>In-frame Harrow</b>	Optional	
<b>Disc Levellers</b>	350 lb. (159 kg) & 550 lb. (249 kg)	
<b>Trip Assemblies:</b>	350 lb. (159 kg) & 550 lb. (249 kg)	
7.5" (19.0 cm)	1 (2.5) x 2 (5.0) 50° C-shank	
10" (25.4 cm) & 12" (30.5 cm)	1 (2.5) x 2 (5.0) 84° edge-on	
<b>Shank, in. (cm)</b>	26 (66)	
	108 (274)	
<b>Rank to Rank Spacing, in. (cm)</b>	148 (376) at 1 (2.5) of seeding depth	
<b>Frame Depth, in. (cm)</b>	28 (71) to 32 (81) (depending on openers)	
<b>Caster to Packer Depth, in. (cm)</b>	High quality parallel cylinders performing both depth and wing lift functions	
<b>Frame/Ground Clearance, in. (cm)</b>	Each wing follows ground independently (not affecting adjacent sections);	
<b>Hydraulic System</b>	independently controlled hydraulically; single-point adjustment	
<b>Depth Control</b>	Standard	
	Standard	
<b>Safety Chain and Lights</b>	Optional; patented steering design to aid in cornering and limit sidehill skewing	
<b>Transport Locks</b>	Each frame section independently adjustable	
<b>Rear Tow Hitch</b>		
<b>Packing Pressure Adjustment</b>		

Every effort has been made to produce these specifications with the most current information available. However, ongoing product development and improvements mean that the equipment and specifications are subject to change without notice.

For up-to-date specifications, product feature details, or to locate your Flexi-Coil dealer, go to

**[WWW.FLEXICOIL.COM](http://WWW.FLEXICOIL.COM)**

It's your direct source for product information and much more.

