

C SERIES LOADER BACKHOES



BUILD MORE TIME INTO YOUR DAY

The C Series loader backhoes offer a model to match your needs. These backhoes feature a straight loader arm design that improves visibility to the bucket top edge and allows machine hydraulic power to lift greater loads. The B95C TC combines the B95C's powerful backhoe with an advanced loader designed to multi-task. The TC's standard quick coupler and self leveling loader make switching from bucket to forks a breeze.

Model	B95C	B95C TC	B110C
Gross HP	97	97	110
Base Unit Weight	17,560 lbs.	17,730 lbs.	18,525 lbs.
Loader SAE Heaped Capacity	1.1 cu. yd.	1.3 cu. yd.	1.3 cu. yd.

Superior Backhoe Design

- Curved boom design of big excavators for outstanding digging performance.
- Narrow boom design improves visibility to trench or bucket
- Optional hydraulically extendable dipper (HED) is internal to put less weight on the extension and affords easier maintenance.

Best-In-Class Accessibility

- Tilting, one-piece, engine hood for excellent ground level access to engine and service points

Ergonomic Cab with Easy Access

- Fully integrated loader control lever
- Plenty of foot room for easy seat rotation to backhoe
- Adjustable seat with armrests
- Open canopy operator's structure available

Stability

- Optional Glide Ride
- Standard return-to-dig
- Wide stabilizer stance



NEW HOLLAND COMPARISONS

AEM Class Gross Power (HP)	Brand	Model	Gross HP	Max Dig Depth (Standard) (ft. in.)	Loader Lift Capacity @ Full Height (lbs.)	Operating Weight (lbs.)
80 < 100	New Holland	B95C	97	14' 6"	7996	17560
	Case	580N	90	14' 8"	6803	17751
	Case	580 Super N	97	14' 4"	7044	19067
	John Deere	310L	100	14' 1"	NA	14669
	Caterpillar	416	86	14'	NA	24251
	Caterpillar	416F2	87	14' 3"	NA	24251
	Caterpillar	420	92	14'	NA	24251
	Caterpillar	420F2	93	14' 3"	NA	24251
	Caterpillar	420 XE	92	14'	NA	24251
100 +	New Holland	B110C	110	15' 6"	7833	18525
	Case	580 Super N WT	110	14' 5"	8425	20077
	Case	590 Super N	110	15' 5"	8202	20532
	John Deere	310SL	103	14' 3"	NA	15872
	John Deere	310SL HL	113	15' 1"	NA	16571
	John Deere	315SL	103	13' 5"	NA	17554
	John Deere	410L	116	15' 11"	NA	17186
	John Deere	710L	148	17' 3"	NA	25588
	Caterpillar	430	107	15' 1"	NA	24251
	Caterpillar	430F2	108	15' 4"	NA	24251
	Caterpillar	440	104	15' 5"	NA	29321
	Caterpillar	450	131	17'	NA	29321
	JCB	3CX-14 SUPER	109	18' 6"	NA	NA
	JCB	3CX-15 SUPER	109	20' 1"	NA	NA
	JCB	4CX-15 SUPER	109	20' 1"	NA	NA
	JCB	4CX-14 SUPER	109	18' 6"	NA	NA

NOTABLE FACTORY OPTIONS

- Hydraulic Options
 - Backhoe hammer circuit
 - 1way/2way auxiliaries for thumb
 - Extra function BH valve with control pedal
 - Glide Ride
- Loader
 - Mechanical Quick Coupler (B95C and B110C)
 - Auxiliary hydraulic
- Backhoe Controls
 - 2-lever pilot controls
 - 4-lever controls
 - 2-lever ISO excavator pattern controls
 - HED extendable dipper
 - Reversible stabilizer pads
- CAB or Open Station (Canopy)



Learn more at www.newholland.com

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.

© 2021 CNH Industrial America LLC. All rights reserved. New Holland is a trademark in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.

NHC713021819 • 0821 • OTP • PRINTED IN U.S.A.