

# D SERIES TRACTOR LOADER BACKHOES



## BUILD MORE TIME INTO YOUR DAY

The D Series tractor loader backhoes offer a model to match your needs. These backhoes feature a straight loader arm design that improves visibility to the bucket top edge and provided greater lift capacity. The B95D TC combines the powerful B95D backhoe with an advanced loader designed to multi-task. The TC's standard quick coupler and self leveling loader make switching from bucket to forks a breeze.

Model	B75D	B95D	B95D TC	B110D
Gross HP	74	97	97	110
Base Unit Weight	17,488 lbs.	17,560 lbs.	17,730 lbs.	18,525 lbs.
Loader Cap, cu. yd.	1.3 cu. yd.	1.3 cu. yd.	1.3 cu. yd.	1.3 cu. yd.

### Superior Backhoe Design

- Curved boom design of big excavators for outstanding digging performance.
- Narrow boom design improves visibility to trench or bucket
- Optional hydraulically extendable dipper (HED) is internal to put less weight on the extension and affords easier maintenance.

### Best-In-Class Accessibility

- Tilting, one-piece, engine hood for excellent ground level access to engine and service points

### Ergonomic Cab with Easy Access

- Fully integrated loader control lever
- Plenty of foot room for easy seat rotation to backhoe
- Adjustable seat with armrests
- Open canopy operator's structure available

### Stability

- Optional Glide Ride
- Standard return-to-dig
- Wide stabilizer stance



## MODEL COMPARISON

AEM Class Gross Power (HP)	Manufacturer	Model	Gross HP	Dig Depth (Standard) (ft. in.)	Loader Lift Capacity @ Full Height (lbs.)	Operating Weight (lbs.)
0 < 75	New Holland	B75D	74	14' 6"	8157	17488
	John Deere	310 L EP	72	14' 1"	6443	13822
	Caterpillar	415 F 2	74	14' 3"	6750	14150
	Kubota	M62	63	14' 1"	3960	8952
	JCB	3CX	74	10'	6354	13514
80 < 100	New Holland	B95D	97	14' 6"	7833	17560
	Case	580N	90	14' 8"	6803	17751
	Case	580 SUPER N	97	14' 4"	7044	19067
	John Deere	310L	100	14' 1"	NA	14669
	Caterpillar	416	86	14'	NA	24251
	Caterpillar	416F2	87	14' 3"	NA	24251
	Caterpillar	420	92	14'	NA	24251
	Caterpillar	420F2	93	14' 3"	NA	24251
100 +	Caterpillar	420 XE	92	14'	NA	24251
	New Holland	B110D	110	15' 6"	7833	18525
	Case	580 Super N WT	110	14' 5"	8425	20077
	Case	590 Super N	110	15' 5"	8202	20532
	John Deere	310SL	103	14' 3"	NA	15872
	John Deere	310SL HL	113	15' 1"	NA	16571
	John Deere	315SL	103	13' 5"	NA	17554
	John Deere	410L	116	15' 11"	NA	17186
	John Deere	710L	148	17' 3"	NA	25588
	Caterpillar	430	107	15' 1"	NA	24251
	Caterpillar	430F2	108	15' 4"	NA	24251
	Caterpillar	440	104	15' 5"	NA	29321
	Caterpillar	450	131	17'	NA	29321
	JCB	3CX-14 SUPER	109	18' 6"	NA	NA
	JCB	3CX-15 SUPER	109	20' 1"	NA	NA
JCB	4CX-15 SUPER	109	20' 1"	NA	NA	
JCB	4CX-14 SUPER	109	18' 6"	NA	NA	



Learn more at [www.newholland.com](http://www.newholland.com)

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.

© 2022 CNH Industrial America LLC. All rights reserved. New Holland is a trademark in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.